

**UNITED STATES PATENT APPLICATION**

**FOR**

**DYNAMIC REPLICATION OF FILES IN A NETWORK  
STORAGE SYSTEM**

Inventor(s)

Joshua Coates


Patrick Bozeman

**CERTIFICATE OF MAILING BY "EXPRESS MAIL"**

Express Mail Label No.: EL714233415US

Date of Deposit: December 29, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to: Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231.



John Stattler, Reg. No. 36,285

## TITLE OF THE INVENTION

DYNAMIC REPLICATION OF FILES IN A NETWORK STORAGE SYSTEM

## CROSS-REFERENCES TO RELATED APPLICATIONS

5

This application claims the benefit of U.S. Patent Application No. 09/695,499, filed October 23, 2000, entitled "A Network Storage System", and to U.S. Provisional Patent Applications Nos. 60/186,693 and 60/186,774, filed March 3, 2000, entitled "Method and Apparatus for Implementing A Network-Based Storage Service" and "Method and Apparatus for Establishing Control and Data Lines To A Storage Facility, And API For Supporting Such Lines", respectively.

10

## BACKGROUND OF THE INVENTION

### Field of the Invention:

The present invention is directed toward the field of storage, and more particularly toward accessing remote storage through use of a local device.

### Art Background:

With the rapid digitization of music, film and photographs, customer demand is driving the Internet to become the most preferred transport mechanism for all forms of digital media. Using the Internet, users have instantaneous worldwide access to their favorite movies, songs, or personal memorabilia. As the producers and owners of media content increasingly use the Internet as a primary method for worldwide distribution, the aggregate

20

amount of rich media content available over the Internet is increasing at an extremely rapid rate.

Not only is the number of rich media objects available over the Internet growing exponentially, but the size of the media, generally referred to herein as objects, is also dramatically increasing. A median Web object is 5 kilobytes (KB) in size, while the size of a rich media object may be 100 to 1 million times larger. For example, high-resolution digital photographs average 500 KB per picture. Digital music runs 3 to 5 megabytes ("MB") per song, and digital movies may reach up to 4 gigabytes ("GB") in size.

As the number of personal computers, digital camcorders, digital cameras, and personal digital audio players grow, demand for Internet bandwidth to store, share and retrieve media files across the Internet also will grow. As the use of high-bandwidth digital subscriber lines ("DSL"), cable modems, and digital broadcast satellite networks gain in popularity, which supports the growth of the Internet backbone, the demand for using the Internet as a primary delivery channel for rich media objects also gains in popularity. This development causes a virtuous cycle, where the installation of broadband networks drives the use of rich media devices, which in turn, creates demand for further improvements in network bandwidth, and so on.

The distribution of rich media objects across the Internet creates the need for increased storage capacity to store these rich media objects. As the number of personal media devices grows, and the network bandwidth expands, the amount of storage media required to store the various MP3 files, photographs, films, and video clips will also grow. Also, as more storage

becomes readily available, more people will use the Internet to catalog, store, and access their rich media objects (e.g., digital photographs of family members).

To date, only traditional storage solutions from established enterprise vendors have been available to a Web site developer implementing rich media repositories. One challenge with adopting today's existing storage technology for use with the Internet is meeting current and future scalability requirements. Today, large scale storage systems only scale to a few dozen terabytes. This amount of storage space is inadequate for storing substantial amounts of rich media objects. For example, if just 10 percent of America on line ("AOL") users place two 15 minute videos on a personal home page, then one petabyte (*i.e.*, 1000 terabytes) of storage would be required. Today's enterprise storage system architectures cannot support this level of storage capacity.

In the Internet world, in addition to providing mass storage, it is also critically important to provide universal access to that storage across the wide area network. The content provider, regardless of the location of their content servers, cache servers, or stream servers, would ideally like to provide ubiquitous access to an entire store of rich media objects. Current technology, including storage area networks and network attached storage technologies, do not provide direct access to the wide area network. Only servers located within the same metropolitan area can directly access these types of storage systems.

Since Internet users are measured in the tens of thousands or even millions of users, instead of hundreds of users, another challenge in mass storage is the ability to scale delivery of media as the demand increases. A true Internet based storage system must be able to

handle peak loads of millions of simultaneous requests from all around the world. Traditional storage architectures are designed to support a few hundred simultaneous requests from the fastest possible response time to match the speed of the server CPU. For the Internet, storage systems must be able to manage literally millions of simultaneous downloads at the speed of the wide area network. Thus, these traditional storage architectures are not “impedance matched” with the wide area network because the storage devices handle far too few simultaneous transactions that far exceed the latency requirements of the wide area network. In addition, these traditional storage architectures are typically implemented with expensive disks and expensive connection technologies.

Another issue regarding storage of rich media objects is the time to market. The time to market is often a crucial requirement for new rich media Web sites. Growth rates are measured in terabytes per month. Quickly bringing new capacity online becomes a strategic advantage in fast-moving markets. Typically, with traditional storage solutions, it takes a customer two to six months to integrate a fully operational multi-terabytes storage unit with the content providers site. This start-up time is too slow to meet rapidly increasing business demands. Pre-building large amounts of excess capacity in anticipation of this demand is one tactic to deal with unpredictable demand spikes, but this approach is prohibitively expensive.

Traditional storage architectures have been optimized for database and file server applications. The Internet introduces a whole new set of demands on storage devices, including scalability, global access, user accounts, and rapid deployment. With the explosive growth in rich media served over the Internet over the next several years, this is coming to a head. The coming tide wave of rich content will surpass the capabilities of even the most

robust enterprise storage architectures. Accordingly, there is a demand to develop new paradigms in new ways of designing Internet ready rich media storage systems.

### SUMMARY OF THE INVENTION

5 A network storage system dynamically allocates files to cache. The dynamic allocation of files in caches is based on requests for the files to the network storage system. The network storage system stores the files in a plurality of intelligent storage nodes. A plurality of control nodes (*e.g.*, distributed object storage manager) processes request to retrieve files from the intelligent storage nodes. For each file request, a control node is selected. In one embodiment, the network storage system utilizes a level four switch with load balancing capabilities to select control nodes. To process the file request, the control node retrieves the file from an intelligent storage node that stores the file, and stores the file retrieved in a cache at the control node. Under this configuration, the selection of control nodes to process a request to retrieve files results in storing files in the caches of the control nodes based on demand for the file.

10  
15  
20 The storage system may include more than one storage center. Each storage center includes control nodes, which contain a cache, and intelligent storage nodes. The storage centers are coupled via a network, such that control nodes of a first storage center may access intelligent storage nodes of a second storage center. As file requests are received at control nodes in the first storage center, files, stored at the second storage center, are retrieved and cached at the first storage center. Thus, processing requests in the first storage center to

retrieve files from the second storage center dynamically stores files in the caches of the control nodes in the first storage center.

### BRIEF DESCRIPTION OF THE DRAWINGS

5           Figure 1 is a block diagram illustrating one embodiment for the storage system of the present invention.

Figure 2 illustrates one embodiment for use of the network storage system as a media storage service.

Figure 3 is a block diagram illustrating one embodiment for the storage cluster.

10           Figure 4 is a flow diagram illustrating one embodiment for the download operation in the storage cluster.

Figure 5 is a flowchart illustrating one embodiment for authentication in the network storage system.

15           Figure 6 illustrates one embodiment of a distributed object storage manager (“DOSM”).

Figure 7 is a block diagram illustrating one embodiment for an intelligent storage node.

Figure 8 is a flow diagram illustrating one embodiment for processing upload requests in the storage cluster.

Figure 9 is a flow diagram illustrating one embodiment for generating unique fingerprints of object files.

Figure 10 is a block diagram illustrating one embodiment for caching data in the storage cluster.

5 Figure 11 is a block diagram illustrating one embodiment for implementing a VFS for use with a network storage system.

Figure 12 illustrates example database tables for implementing the file system with a database.

10 Figures 13A and 13B are flow diagrams illustrating one embodiment for performing directory operations in the VFS.

Figure 14 is a flow diagram illustrating one embodiment for the delete file operation for the network storage system.

Figure 15 illustrates geographical replications of storage centers.

15 Figure 16 is a block diagram illustrating one embodiment for replicating the storage centers.

Figure 17 illustrates one embodiment for use of the storage center in a content delivery network.

Figure 18 is a flow diagram illustrating one embodiment for use of the storage center with a content delivery network.



Figure 19 illustrates one embodiment for use of the storage port in the network storage system.

Figure 20 is a flow diagram illustrating one embodiment for use of a storage port to deliver content.

5 Figure 21a illustrates one hardware configuration for a storage port device.

Figure 21b illustrates embodiments for implementing the storage port in software.

Figure 22 is a block diagram illustrating one embodiment for a storage port.

Figure 23 is a block diagram illustrating one embodiment for file system translation in the storage port.

10 Figure 24 is a flow diagram illustrating one embodiment for translating a file system operation from a local file system to the network storage file system.

Figure 25 is a block diagram illustrating one embodiment for using the storage port to directly download object files to the end-user.

15 Figure 26 is a flow diagram illustrating one embodiment for directly downloading object files to an end-user.

Figure 27 is a block diagram illustrating one embodiment to interface a storage center to a client's private file directory system.

Figure 28 is a flow diagram illustrating one embodiment for accessing object files in a storage center using a client's private file system.

Figure 29 is a block diagram illustrating one embodiment for a storage port fail over configuration.

5 Figure 30 is a flow diagram illustrating one embodiment for a storage port fail over process.

Figure 31 is a flow diagram illustrating one embodiment for using the multicast protocol after a storage node fail over condition.

### DETAILED DESCRIPTION

10 The disclosure of U.S. Provisional Patent Applications Nos. 60/186,693 and 60/186,774, filed March 3, 2000, entitled "Method and Apparatus for Implementing A Network-Based Storage Service" and "Method and Apparatus for Establishing Control and Data Lines To A Storage Facility, And API For Supporting Such Lines", respectively, are hereby incorporated by reference.

#### Network Storage System Overview:

15 The network storage system is designed to meet the storage requirements of rich media content owners. Rich media objects typically represent up to 90 percent of the storage required for a film, music or a photo album associated with a web site. The network storage  
20 system uses distributed systems technology to provide scalability to support petabytes of storage and to support millions of users. Users only gain access to their media objects, within

the network storage system, using a highly secured “shared secret” authentication certificate technology. The network storage system also provides immediate expandability for any user that desires to increase their storage capacity. Also, the network storage system is extremely cost-effective because, in one embodiment, it consists of standard off the shelf CPUs with the latest high-density disk technology.

For purposes of nomenclature, the term “client”, as used herein, refers to an entity that uses the storage system to store object files. For example, a client may consist of a web site owner that desires to deliver, outside their web server, rich media objects associated with content on their web site. Also, for purposes of nomenclature, the term “end-user”, as used herein, refers to a recipient of the object. For example, the end-user may consist of a computer user that downloads objects from a web site across the Internet using a web browser. Also, under this definition, the end-user may also be a client.

Figure 1 is a block diagram illustrating one embodiment for the storage system of the present invention. For the embodiment of Figure 1, the storage system consists of a control path and a data path. The control path consists of a virtual file system (“VFS”) 50 and the data path consists of a distributed storage cluster 70. The control path is used to conduct all directory operations. The VFS includes, in part, client assigned filenames and network storage system assigned unique file identifiers for each rich media object. The unique file identifiers are embedded into storage resource locators (“SRLs”).

The distributed storage cluster 70 is used to store the object files for the system (*i.e.*, all client data). As shown in Figure 1, the VFS and the storage cluster 70 are coupled to

communicate information so as to coordinate file system information with the physical storage of the object files.

As shown in Figure 1, file system control 60 issues directory operation requests to the VFS 50. As is described more fully below, file system control 60 may comprise software that uses a library to essentially “translate” file system requests from the client’s local file system to file system requests compatible with the network storage system. In other embodiments, file system control 60 consists of a storage port coupled to the client’s system (*e.g.*, the client’s application or web server). In general, the storage port, implemented in either hardware or software, translates file system commands from the client’s local file system (*e.g.*, NFS or CIFS) to file system requests compatible with the network storage system. In one embodiment, to interface the client’s file system to the network storage system, a client need only mount the storage port as a network drive. The storage port then provides complete access to the network storage system. A detailed discussion of the storage port is set forth below.

As shown in Figure 1, object recipient 80 receives, in response to object requests, objects downloaded from storage cluster 70. The object recipient 80 may comprise the client, or the object recipient 80 may consist of one or more end-users. Embodiments for transferring objects from the storage cluster 70 to object recipients, including both end-users and clients, are described more fully below.

The network storage system has applications for use as an Internet based media storage service. For this application, the network storage system is an integral part of the Internet

infrastructure used by rich media content owners and delivery networks. Figure 2 illustrates one embodiment for use of the network storage system as a media storage service. In general, the storage service 130 provides a single consistent worldwide image of a client's (*e.g.*, a company operating a web site) entire directory of rich objects. For this embodiment, an end-  
5 user 100 is coupled to both the content origin server 120 and storage service 130 through a network. For example, the end-user 100 may be coupled to the content origin server 120 and storage service 130 via the Internet. The storage service 130 includes processing and networking facilities, such as a server 140, and data store 150. The storage service 130 and content origin server 120 communicate to conduct file directory operations and object file  
10 operations. The data store 150, part of the storage service 130, stores large data files, such as rich media data files, illustrated as multimedia files 160, 170 and 180 in Figure 2. In one embodiment, the data store 150 consists of a cluster of intelligent storage nodes.

In one embodiment, the storage service communicates with web servers (*e.g.*, content origin server 120) and browsers (*e.g.*, Microsoft Explorer or Netscape Navigator) operating on end-user computer 100 via the standard Internet hypertext transfer protocol ("HTTP") and universal resource locators ("URLs"). Although the use of HTTP is described herein, any transport protocol may be used without deviating from the spirit or scope of the invention. For the configuration of Figure 2, the end-user, through end-user computer 100, generates hyper text transfer protocol ("HTTP") requests to the content origin server 120 to obtain hyper  
15 text mark-up language ("HTML") files. In addition, to obtain large data objects associated with those text files, the end-user, through end user computer 100, generates HTTP requests to  
20 the storage service 130. For example, the end-user may download from the content origins

server 120 a few kilobytes of textual data describing a rich object, such as text describing an upcoming film. When the user “clicks” on a URL to download a film snippet from the upcoming film, an HTTP request is generated to the storage service 130, and a storage service 130 downloads the film snippet to the end-user computer 100. The network configuration of Figure 2 permits off loading the storage of rich objects from the content origin server 120 to the storage service 130. This configuration greatly reduces the size and complexity of content origin servers needed to store, manage and serve rich objects to end-users.

#### Distributed Storage Cluster:

In one embodiment, the storage cluster utilizes distributed systems technology that harnesses the throughput of hundreds of CPUs and the storage of thousands of disk drives. Figure 3 is a block diagram illustrating one embodiment for the storage cluster. The storage cluster 300 receives upload, download, and delete operations that include the storage resource locator (“SRL”). The SRL is then used to uniquely identify a client file. As shown in Figure 3, the storage cluster consists of distributed object storage managers (“DOSMs”) 320 and intelligent storage nodes 340. There are “n” distributed object storage managers 320, wherein “n” is any integer value greater than one. Similarly, there are “n” intelligent storage nodes for the intelligent storage nodes 340 component (*i.e.*, wherein “n” is also any integer value greater than one).

As shown in Figure 3, file upload and download operations are input to a load balancing fabric 310. In one embodiment, the load balancing fabric 310 is a layer four (“L4”) switch. In general, L4 switches are capable of effectively prioritizing TCP and UDP traffic.

10  
5 In addition, L4 switches, which incorporate load balancing capabilities, distribute requests for HTTP sessions among a number of resources, such as servers. For this embodiment, the load balancing fabric 310 distributes upload and download requests to one of a plurality of DOSMs based on DOSM availability. The load balancing capability in an L4 switch is currently commercially available.

Each DOSM independently handles hundreds of simultaneous download transactions. In one embodiment described below, each DOSM has a local high-speed disk cache to store frequently accessed file objects. Each DOSM has a map, dynamically generated, of the storage system. The map identifies a correspondence between an intelligent storage node address and an object finger print. In one embodiment, the DOSMs record all usage and performance data gathered by a separate accounting system and monitoring system.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995  
1000  
1005  
1010  
1015  
1020  
1025  
1030  
1035  
1040  
1045  
1050  
1055  
1060  
1065  
1070  
1075  
1080  
1085  
1090  
1095  
1100  
1105  
1110  
1115  
1120  
1125  
1130  
1135  
1140  
1145  
1150  
1155  
1160  
1165  
1170  
1175  
1180  
1185  
1190  
1195  
1200  
1205  
1210  
1215  
1220  
1225  
1230  
1235  
1240  
1245  
1250  
1255  
1260  
1265  
1270  
1275  
1280  
1285  
1290  
1295  
1300  
1305  
1310  
1315  
1320  
1325  
1330  
1335  
1340  
1345  
1350  
1355  
1360  
1365  
1370  
1375  
1380  
1385  
1390  
1395  
1400  
1405  
1410  
1415  
1420  
1425  
1430  
1435  
1440  
1445  
1450  
1455  
1460  
1465  
1470  
1475  
1480  
1485  
1490  
1495  
1500  
1505  
1510  
1515  
1520  
1525  
1530  
1535  
1540  
1545  
1550  
1555  
1560  
1565  
1570  
1575  
1580  
1585  
1590  
1595  
1600  
1605  
1610  
1615  
1620  
1625  
1630  
1635  
1640  
1645  
1650  
1655  
1660  
1665  
1670  
1675  
1680  
1685  
1690  
1695  
1700  
1705  
1710  
1715  
1720  
1725  
1730  
1735  
1740  
1745  
1750  
1755  
1760  
1765  
1770  
1775  
1780  
1785  
1790  
1795  
1800  
1805  
1810  
1815  
1820  
1825  
1830  
1835  
1840  
1845  
1850  
1855  
1860  
1865  
1870  
1875  
1880  
1885  
1890  
1895  
1900  
1905  
1910  
1915  
1920  
1925  
1930  
1935  
1940  
1945  
1950  
1955  
1960  
1965  
1970  
1975  
1980  
1985  
1990  
1995  
2000  
2005  
2010  
2015  
2020  
2025  
2030  
2035  
2040  
2045  
2050  
2055  
2060  
2065  
2070  
2075  
2080  
2085  
2090  
2095  
2100  
2105  
2110  
2115  
2120  
2125  
2130  
2135  
2140  
2145  
2150  
2155  
2160  
2165  
2170  
2175  
2180  
2185  
2190  
2195  
2200  
2205  
2210  
2215  
2220  
2225  
2230  
2235  
2240  
2245  
2250  
2255  
2260  
2265  
2270  
2275  
2280  
2285  
2290  
2295  
2300  
2305  
2310  
2315  
2320  
2325  
2330  
2335  
2340  
2345  
2350  
2355  
2360  
2365  
2370  
2375  
2380  
2385  
2390  
2395  
2400  
2405  
2410  
2415  
2420  
2425  
2430  
2435  
2440  
2445  
2450  
2455  
2460  
2465  
2470  
2475  
2480  
2485  
2490  
2495  
2500  
2505  
2510  
2515  
2520  
2525  
2530  
2535  
2540  
2545  
2550  
2555  
2560  
2565  
2570  
2575  
2580  
2585  
2590  
2595  
2600  
2605  
2610  
2615  
2620  
2625  
2630  
2635  
2640  
2645  
2650  
2655  
2660  
2665  
2670  
2675  
2680  
2685  
2690  
2695  
2700  
2705  
2710  
2715  
2720  
2725  
2730  
2735  
2740  
2745  
2750  
2755  
2760  
2765  
2770  
2775  
2780  
2785  
2790  
2795  
2800  
2805  
2810  
2815  
2820  
2825  
2830  
2835  
2840  
2845  
2850  
2855  
2860  
2865  
2870  
2875  
2880  
2885  
2890  
2895  
2900  
2905  
2910  
2915  
2920  
2925  
2930  
2935  
2940  
2945  
2950  
2955  
2960  
2965  
2970  
2975  
2980  
2985  
2990  
2995  
3000  
3005  
3010  
3015  
3020  
3025  
3030  
3035  
3040  
3045  
3050  
3055  
3060  
3065  
3070  
3075  
3080  
3085  
3090  
3095  
3100  
3105  
3110  
3115  
3120  
3125  
3130  
3135  
3140  
3145  
3150  
3155  
3160  
3165  
3170  
3175  
3180  
3185  
3190  
3195  
3200  
3205  
3210  
3215  
3220  
3225  
3230  
3235  
3240  
3245  
3250  
3255  
3260  
3265  
3270  
3275  
3280  
3285  
3290  
3295  
3300  
3305  
3310  
3315  
3320  
3325  
3330  
3335  
3340  
3345  
3350  
3355  
3360  
3365  
3370  
3375  
3380  
3385  
3390  
3395  
3400  
3405  
3410  
3415  
3420  
3425  
3430  
3435  
3440  
3445  
3450  
3455  
3460  
3465  
3470  
3475  
3480  
3485  
3490  
3495  
3500  
3505  
3510  
3515  
3520  
3525  
3530  
3535  
3540  
3545  
3550  
3555  
3560  
3565  
3570  
3575  
3580  
3585  
3590  
3595  
3600  
3605  
3610  
3615  
3620  
3625  
3630  
3635  
3640  
3645  
3650  
3655  
3660  
3665  
3670  
3675  
3680  
3685  
3690  
3695  
3700  
3705  
3710  
3715  
3720  
3725  
3730  
3735  
3740  
3745  
3750  
3755  
3760  
3765  
3770  
3775  
3780  
3785  
3790  
3795  
3800  
3805  
3810  
3815  
3820  
3825  
3830  
3835  
3840  
3845  
3850  
3855  
3860  
3865  
3870  
3875  
3880  
3885  
3890  
3895  
3900  
3905  
3910  
3915  
3920  
3925  
3930  
3935  
3940  
3945  
3950  
3955  
3960  
3965  
3970  
3975  
3980  
3985  
3990  
3995  
4000  
4005  
4010  
4015  
4020  
4025  
4030  
4035  
4040  
4045  
4050  
4055  
4060  
4065  
4070  
4075  
4080  
4085  
4090  
4095  
4100  
4105  
4110  
4115  
4120  
4125  
4130  
4135  
4140  
4145  
4150  
4155  
4160  
4165  
4170  
4175  
4180  
4185  
4190  
4195  
4200  
4205  
4210  
4215  
4220  
4225  
4230  
4235  
4240  
4245  
4250  
4255  
4260  
4265  
4270  
4275  
4280  
4285  
4290  
4295  
4300  
4305  
4310  
4315  
4320  
4325  
4330  
4335  
4340  
4345  
4350  
4355  
4360  
4365  
4370  
4375  
4380  
4385  
4390  
4395  
4400  
4405  
4410  
4415  
4420  
4425  
4430  
4435  
4440  
4445  
4450  
4455  
4460  
4465  
4470  
4475  
4480  
4485  
4490  
4495  
4500  
4505  
4510  
4515  
4520  
4525  
4530  
4535  
4540  
4545  
4550  
4555  
4560  
4565  
4570  
4575  
4580  
4585  
4590  
4595  
4600  
4605  
4610  
4615  
4620  
4625  
4630  
4635  
4640  
4645  
4650  
4655  
4660  
4665  
4670  
4675  
4680  
4685  
4690  
4695  
4700  
4705  
4710  
4715  
4720  
4725  
4730  
4735  
4740  
4745  
4750  
4755  
4760  
4765  
4770  
4775  
4780  
4785  
4790  
4795  
4800  
4805  
4810  
4815  
4820  
4825  
4830  
4835  
4840  
4845  
4850  
4855  
4860  
4865  
4870  
4875  
4880  
4885  
4890  
4895  
4900  
4905  
4910  
4915  
4920  
4925  
4930  
4935  
4940  
4945  
4950  
4955  
4960  
4965  
4970  
4975  
4980  
4985  
4990  
4995  
5000  
5005  
5010  
5015  
5020  
5025  
5030  
5035  
5040  
5045  
5050  
5055  
5060  
5065  
5070  
5075  
5080  
5085  
5090  
5095  
5100  
5105  
5110  
5115  
5120  
5125  
5130  
5135  
5140  
5145  
5150  
5155  
5160  
5165  
5170  
5175  
5180  
5185  
5190  
5195  
5200  
5205  
5210  
5215  
5220  
5225  
5230  
5235  
5240  
5245  
5250  
5255  
5260  
5265  
5270  
5275  
5280  
5285  
5290  
5295  
5300  
5305  
5310  
5315  
5320  
5325  
5330  
5335  
5340  
5345  
5350  
5355  
5360  
5365  
5370  
5375  
5380  
5385  
5390  
5395  
5400  
5405  
5410  
5415  
5420  
5425  
5430  
5435  
5440  
5445  
5450  
5455  
5460  
5465  
5470  
5475  
5480  
5485  
5490  
5495  
5500  
5505  
5510  
5515  
5520  
5525  
5530  
5535  
5540  
5545  
5550  
5555  
5560  
5565  
5570  
5575  
5580  
5585  
5590  
5595  
5600  
5605  
5610  
5615  
5620  
5625  
5630  
5635  
5640  
5645  
5650  
5655  
5660  
5665  
5670  
5675  
5680  
5685  
5690  
5695  
5700  
5705  
5710  
5715  
5720  
5725  
5730  
5735  
5740  
5745  
5750  
5755  
5760  
5765  
5770  
5775  
5780  
5785  
5790  
5795  
5800  
5805  
5810  
5815  
5820  
5825  
5830  
5835  
5840  
5845  
5850  
5855  
5860  
5865  
5870  
5875  
5880  
5885  
5890  
5895  
5900  
5905  
5910  
5915  
5920  
5925  
5930  
5935  
5940  
5945  
5950  
5955  
5960  
5965  
5970  
5975  
5980  
5985  
5990  
5995  
6000  
6005  
6010  
6015  
6020  
6025  
6030  
6035  
6040  
6045  
6050  
6055  
6060  
6065  
6070  
6075  
6080  
6085  
6090  
6095  
6100  
6105  
6110  
6115  
6120  
6125  
6130  
6135  
6140  
6145  
6150  
6155  
6160  
6165  
6170  
6175  
6180  
6185  
6190  
6195  
6200  
6205  
6210  
6215  
6220  
6225  
6230  
6235  
6240  
6245  
6250  
6255  
6260  
6265  
6270  
6275  
6280  
6285  
6290  
6295  
6300  
6305  
6310  
6315  
6320  
6325  
6330  
6335  
6340  
6345  
6350  
6355  
6360  
6365  
6370  
6375  
6380  
6385  
6390  
6395  
6400  
6405  
6410  
6415  
6420  
6425  
6430  
6435  
6440  
6445  
6450  
6455  
6460  
6465  
6470  
6475  
6480  
6485  
6490  
6495  
6500  
6505  
6510  
6515  
6520  
6525  
6530  
6535  
6540  
6545  
6550  
6555  
6560  
6565  
6570  
6575  
6580  
6585  
6590  
6595  
6600  
6605  
6610  
6615  
6620  
6625  
6630  
6635  
6640  
6645  
6650  
6655  
6660  
6665  
6670  
6675  
6680  
6685  
6690  
6695  
6700  
6705  
6710  
6715  
6720  
6725  
6730  
6735  
6740  
6745  
6750  
6755  
6760  
6765  
6770  
6775  
6780  
6785  
6790  
6795  
6800  
6805  
6810  
6815  
6820  
6825  
6830  
6835  
6840  
6845  
6850  
6855  
6860  
6865  
6870  
6875  
6880  
6885  
6890  
6895  
6900  
6905  
6910  
6915  
6920  
6925  
6930  
6935  
6940  
6945  
6950  
6955  
6960  
6965  
6970  
6975  
6980  
6985  
6990  
6995  
7000  
7005  
7010  
7015  
7020  
7025  
7030  
7035  
7040  
7045  
7050  
7055  
7060  
7065  
7070  
7075  
7080  
7085  
7090  
7095  
7100  
7105  
7110  
7115  
7120  
7125  
7130  
7135  
7140  
7145  
7150  
7155  
7160  
7165  
7170  
7175  
7180  
7185  
7190  
7195  
7200  
7205  
7210  
7215  
7220  
7225  
7230  
7235  
7240  
7245  
7250  
7255  
7260  
7265  
7270  
7275  
7280  
7285  
7290  
7295  
7300  
7305  
7310  
7315  
7320  
7325  
7330  
7335  
7340  
7345  
7350  
7355  
7360  
7365  
7370  
7375  
7380  
7385  
7390  
7395  
7400  
7405  
7410  
7415  
7420  
7425  
7430  
7435  
7440  
7445  
7450  
7455  
7460  
7465  
7470  
7475  
7480  
7485  
7490  
7495  
7500  
7505  
7510  
7515  
7520  
7525  
7530  
7535  
7540  
7545  
7550  
7555  
7560  
7565  
7570  
7575  
7580  
7585  
7590  
7595  
7600  
7605  
7610  
7615  
7620  
7625  
7630  
7635  
7640  
7645  
7650  
7655  
7660  
7665  
7670  
7675  
7680  
7685  
7690  
7695  
7700  
7705  
7710  
7715  
7720  
7725  
7730  
7735  
7740  
7745  
7750  
7755  
7760  
7765  
7770  
7775  
7780  
7785  
7790  
7795  
7800  
7805  
7810  
7815  
7820  
7825  
7830  
7835  
7840  
7845  
7850  
7855  
7860  
7865  
7870  
7875  
7880  
7885  
7890  
7895  
7900  
7905  
7910  
7915  
7920  
7925  
7930  
7935  
7940  
7945  
7950  
7955  
7960  
7965  
7970  
7975  
7980  
7985  
7990  
7995  
8000  
8005  
8010  
8015  
8020  
8025  
8030  
8035  
8040  
8045  
8050  
8055  
8060  
8065  
8070  
8075  
8080  
8085  
8090  
8095  
8100  
8105  
8110  
8115  
8120  
8125  
8130  
8135  
8140  
8145  
8150  
8155  
8160  
8165  
8170  
8175  
8180  
8185  
8190  
8195  
8200  
8205  
8210  
8215  
8220  
8225  
8230  
8235  
8240  
8245  
8250  
8255  
8260  
8265  
8270  
8275  
8280  
8285  
8290  
8295  
8300  
8305  
8310  
8315  
8320  
8325  
8330  
8335  
8340  
8345  
8350  
8355  
8360  
8365  
8370  
8375  
8380  
8385  
8390  
8395  
8400  
8405  
8410  
8415  
8420  
8425  
8430  
8435  
8440  
8445  
8450  
8455  
8460  
8465  
8470  
8475  
8480  
8485  
8490  
8495  
8500  
8505  
8510  
8515  
8520  
8525  
8530  
8535  
8540  
8545  
8550  
8555  
8560  
8565  
8570  
8575  
8580  
8585  
8590  
8595  
8600  
8605  
8610  
8615  
8620  
8625  
8630  
8635  
8640  
8645  
8650  
8655  
8660  
8665  
8670  
8675  
8680  
8685  
8690  
8695  
8700  
8705  
8710  
8715  
8720  
8725  
8730  
8735  
8740  
8745  
8750  
8755  
8760  
8765  
8770  
8775  
8780  
8785  
8790  
8795  
8800  
8805  
8810  
8815  
8820  
8825  
8830  
8835  
8840  
8845  
8850  
8855  
8860  
8865  
8870  
8875  
8880  
8885  
8890  
8895  
8900  
8905  
8910  
8915  
8920  
8925  
8930  
8935  
8940  
8945  
8950  
8955  
8960  
8965  
8970  
8975  
8980  
8985  
8990  
8995  
9000  
9005  
9010  
9015  
9020  
9025  
9030  
9035  
9040  
9045  
9050  
9055  
9060  
9065  
9070  
9075  
9080  
9085  
9090  
9095  
9100  
9105  
9110  
9115  
9120  
9125  
9130  
9135  
9140  
9145  
9150  
9155  
9160  
9165  
9170  
9175  
9180  
9185  
9190  
9195  
9200  
9205  
9210  
9215  
9220  
9225  
9230  
9235  
9240  
9245  
9250  
9255  
9260  
9265  
9270  
9275  
9280  
9285  
9290  
9295  
9300  
9305  
9310  
9315  
9320  
9325  
9330  
9335  
9340  
9345  
9350  
9355  
9360  
9365  
9370  
9375  
9380  
9385  
9390  
9395  
9400  
9405  
9410  
9415  
9420  
9425  
9430  
9435  
9440  
9445  
9450  
9455  
9460  
9465  
9470  
9475  
9480  
9485  
9490  
9495  
9500  
9505  
9510  
9515  
9520  
9525  
9530  
9535  
9540  
9545  
9550  
9555  
9560  
9565  
9570  
9575  
9580  
9585  
9590  
9595  
9600  
9605  
9610  
9615  
9620  
9625  
9630  
9635  
9640  
9645  
9650  
9655  
9660  
9665  
9670  
9675  
9680  
9685  
9690  
9695  
9700  
9705  
9710  
9715  
9720  
9725  
9730  
9735  
9740  
9745  
9750  
9755  
9760  
9765  
9770  
9775  
9780  
9785  
9790  
9795  
9800  
9805  
9810  
9815  
9820  
9825  
9830  
9835  
9840  
9845  
9850  
9855  
9860  
9865  
9870  
9875  
9880  
9885  
9890  
9895  
9900  
9905  
9910  
9915  
9920  
9925  
9930  
9935  
9940  
9945  
9950  
9955  
9960  
9965  
9970  
9975  
9980  
9985  
9990  
9995  
10000  
10005  
10010  
10015  
10020  
10025  
10030  
10035  
10040  
10045  
10050  
10055  
10060  
10065  
10070  
10075  
10080  
10085  
10090  
10095  
10100  
10105  
10110  
10115  
10120  
10125  
10130  
10135  
10140  
10145  
10150  
10155  
10160  
10165  
10170  
10175  
10180  
10185  
10190  
10195  
10200  
10205  
10210  
10215  
10220  
10225  
10230  
10235  
10240  
10245  
1025

intelligent storage nodes are described more fully below in conjunction with the discussion of Figure 7.

In one embodiment, the network storage system uses the storage resource locators ("SRLs") to process requests. In one embodiment, the network storage system uses the following format for the SRL:

http://<storage-cluster>/<encoded-request>/<digital-signature>/<arbitrary-customer-uri,

wherein:

the "storage-cluster" field includes the name or IP address of a storage center DSM pool;

the "encoded-request" field comprises a base64 encoded op code and arguments;

the "digital-signature" field consists of a certificate derived from the following expression: md5( shared-secret + md5( shared-secret + encoded-request)); and

the "arbitrary-customer-uri" field contains arbitrary information added to the SRL by the network storage system clients. For example, the arbitrary-customer-uri field may include the filename and extension of the file being downloaded to enable browsers to send the content to an appropriate plug-in.

In one embodiment, the "encoded request" field is encoded using base64 encoding. As shown in Table 1, the encoded request consists of a URL type field, a version field, and type/version specific payload field.



**Table 1**

Field	Datatype	Comment
Type	Numeric	Type of the URL, i.e. Standard, CDN, etc.
Version	Numeric	Version of the URL
Payload	NA	Payload specific to the Type/Version of the URL.

In one embodiment, the type/version specific payload field consists of a series of '/' delimited fields that contain accounting information, an op code, and an op code dependent argument list. Table 2 shows one embodiment for the type/version specific payload field.

**Table 2**

Field	Datatype	Comment
Expires	Numeric	Number of seconds since the epoc that the link expires. If 0, the link has an infinite duration and will not be checked for expiration.
Access method	Numeric	The access method associated with the SRL, i.e. Storage Port, end user SRL, CDN, etc.
Client Id	Numeric	The client id of the client performing the operation.
Op Code	Numeric	The opcode of the operation to be performed.
Arguments	NA	An opcode specific argument list.

Table 3 includes two access method types for the access method field.

**Table 3**

<b>Access method</b>	<b>Encoding</b>	<b>Comment</b>
SRL	0x0001	End user SRL request.
Storage Port	0x0002	Internal Storage Port request.

Table 4 includes operational codes for the op code field.

**Table 4**

<b>Operation</b>	<b>Encoding</b>	<b>Arguments</b>
NO_OP	0x0000	None
STORE	0x0010	Pfid – numeric Parent folder id to upload the file to. Other arguments are mime encoded.
FETCH	0x0020	Md5 – alphanumeric Hexadecimal representation of the md5 hash of the file to be downloaded.
FETCH_AUTH	0x0021	Md5 – alphanumeric Hexadecimal representation of the md5 hash of the file to be downloaded.  Authentication Callback URI – alphanumeric URL encoded callback URI
DELETE	0x0050	Md5 – alphanumeric Hexadecimal representation of the md5 hash of the file to be deleted.
CONTROL	0x1000	ControlTicket – alphanumeric Hexadecimal representation of the digital signature of the XML control document.

5

The object files, stored in one or more storage clusters, are not associated with a “central authority” that specifies a physical location for the object files. The VFS, in part, stores an object fingerprint for a file, but does not indicate a location for the file. Because of this, the network storage system may be referred to as a “stateless” or a “soft state” system.

Instead of using a central authority to locate files, the physical address for the files is identified in the storage cluster through a dynamically generated reference. However, the reference does not necessarily identify the location for all the object files (*i.e.*, the reference, at any one time, potentially identifies only a subset of the object files in the system). Since the network storage system does not use a central authority, object files may be added, updated or stored in multiple locations in the storage system, and the location of the object files in the intelligent storage nodes may be discovered in response to a specific request..

Figure 4 is a flow diagram illustrating one embodiment for the download operation in the storage cluster. For purposes of nomenclature, the “recipient” in a download operation is the destination of the file for the download operation. The storage cluster receives a download request, including the unique file identifier (*e.g.*, SRL) (block 400, Figure 4). When the storage cluster receives a download request, the load balancing fabric 310 (Figure 3), such as an L4 switch, selects an available DOSM (block 410, Figure 4). The DOSM parses the SRL to extract the certificate and the encoded request (block 415, Figure 4). From the encoded request, a certificate is calculated, and the calculated certificate is compared to the SRL certificate. If the SRL does not authenticate, then an error message is sent to the recipient (blocks 420 and 425, Figure 4). Alternatively, if the SRL does authenticate, then the DOSM determines whether the object identified by the SRL resides in the corresponding DOSM’s data cache (blocks 420 and 430, Figure 4). If the data object is cached, then the object is transmitted from the storage cluster to the recipient (*e.g.*, via the Internet using HTTP protocol) (blocks 430 and 495, Figure 4). If the object is not cached at the DOSM, then the

DOSM attempts to identify the location of the object in one of the intelligent storage nodes (blocks 430 and 440, Figure 4).

If the DOSM knows the location of the object (*e.g.*, the object file is an entry in the DOSM look-up table) and the storage node is readable, then the DOSM obtains a connection with the storage node that stores the object, and transmits the object from the storage cluster to the recipient (blocks 442, 435 and 495, Figure 4). In one embodiment, to determine whether the storage node is readable, the DOSM queries the storage node for the object file a predetermined number of times. Alternatively, if the DOSM does not know the storage location of the object in the intelligent storage nodes, then the DOSM broadcasts a request to the intelligent storage nodes to locate the object (blocks 440 and 450, Figure 4). Each intelligent storage node determines whether the object is stored on one of its disk drives (block 460, Figure 4). If the object file is located in one of the intelligent storage nodes, then the intelligent storage node, which stores the requested object, broadcasts identification information to all of the distributed object storage managers (blocks 462 and 470, Figure 4). For example, if intelligent storage node “1” of intelligent storage nodes 340 stores the requested object in disk “3”, then intelligent storage node “1” broadcasts to all “n” DOSMs that the object file is located in disk “3” of intelligent storage node “1.” All DOSMs snoop the packets on the network to obtain file identification information. In response to the intelligent storage nodes broadcast, each DOSM updates its reference (*e.g.*, lookup table or file system directory) with the proper file identification information.

If the DOSM broadcasts a request to the intelligent storage nodes to locate the object and the object is not located from the request, then the DOSM establishes a point-to-point

connection with an intelligent storage node to individually query the storage node for the object (blocks 462 and 464, Figure 4). This process is repeated until all intelligent storage nodes have been queried or the object has been located. If the object is located in one of the intelligent storage nodes, then the intelligent storage node, which stores the requested object, broadcasts identification information to all of the distributed object storage managers (blocks 466 and 470, Figure 4). Alternatively, if the object is not located in one of the intelligent storage nodes, then a failover procedure is executed to locate the object in a different storage center (blocks 466 and 468, Figure 4).

When the intelligent storage node is located, the DOSM obtains a connection with the intelligent storage node, and opens the file with the requested object. If the storage node is readable (*i.e.*, the DOSM successfully reads the file from the storage node), then the object is transmitted from the intelligent storage node to the recipient via a network (*e.g.*, using HTTP protocol over the Internet). If the object file is not readable, then a failover procedure is executed to obtain the object in a different storage node and/or storage center, and the DOSM obtains a connection with the new storage node (blocks 442, 468 and 435, Figure 4). Thereafter, the object is transmitted from the storage cluster to the recipient (block 495, Figure 4).

In one embodiment, accesses to the network storage system require a valid authentication certificate. In one embodiment utilizing CDNs, the certificate is based on the object file's unique user filename and a secure key assigned to each client account. In other embodiments, the network storage system supports full HTTPS and SSL protocols for secure communications between clients/end-users and the network storage system.

Figure 5 is a flowchart illustrating one embodiment for authentication in the network storage system. To authenticate a request, the network storage system decodes the SRL to extract the client identification, the SRL certificate and the client filename or object fingerprint (block 500, Figure 5). The network storage system (*i.e.*, virtual file system or storage cluster) extracts a “secret” or secure key corresponding to the client identified with the request. In general, the “secret” or secure key is a password supplied by the client to authenticate operations in the network storage system. Using the secure key and object fingerprint, the network storage system generates a calculated certificate (block 520, Figure 5). In one embodiment, the network storage system generates a calculated certificate for the request in accordance with the following expression:

$$MD5\ Hash\ (Secure\ Key + MD5\ Hash\ (Secure\ Key + Encoded\ SRL))$$

As shown above, a first MD5 hash calculation is performed on the object fingerprint and the secure key to obtain a first result, and a second MD5 hash calculation is performed on the first result and the secure key to obtain the calculated certificate. The network storage system compares the calculated certificate with the SRL certificate (*i.e.*, the certificate transmitted with the SRL request) (block 530, Figure 5). If the certificates match, then the SRL is authenticated, and the request is performed (blocks 540 and 560, Figure 5). Alternatively, if the calculated certificate does not match the SRL certificate, then the network storage system generates an error message to the requester (blocks 540 and 550, Figure 5).

Figure 6 illustrates one embodiment of a distributed object storage manager (“DOSM”). For this embodiment, the processes and functions of each DOSM (*i.e.*, also

referred to herein as a “control node”) are implemented in software for execution on a computer, such as a server 600. In other embodiments, the distributed object storage managers 320 may be implemented in a combination of hardware and software on one or more computers. Each DOSM maintains a file lookup table to identify the location of object files stored in the intelligent storage nodes 340. Table 610 of Figure 6 illustrates one embodiment for a DOSM file lookup table. For this embodiment, each entry of the table identifies a corresponding object file stored in an intelligent storage node. Specifically, each entry includes a file identification, an IP address, and a disk identification. The file identification, also referred to herein as the object fingerprint, is derived by performing an MD5 hash calculation on the contents of the object file. The result of this MD5 hash calculation is a 128 bit string. For this embodiment, the DOSM file lookup table stores, in the file identification column, the 128 bit string, with the file designation “MD5.” The second column of the DOSM file lookup table stores the IP address of the intelligent storage node that stores the object file (*e.g.*, “10.3.100.1”). The third column, labeled disk ID, stores an integer value that identifies the specific disk drive on the intelligent storage node that stores the object file. In one embodiment, when the look-up table is at full capacity, the DOSM uses a least recently used (“LRU”) caching algorithm to replace existing entries in the DOSM lookup table with new entries received.

As shown in Figure 6, the DOSM also includes a data cache 620. In general, the data cache 620 stores objects (*i.e.*, client data) to permit the DOSM to streamline data directly to the recipient in response to a download request. During a download request, in the event of a cache miss, when the object is transferred from the intelligent storage node to the recipient,

the object is also stored in the data cache 620. Similar to the DOSM file lookup table, the data cache 620 uses a least recently used (“LRU”) caching algorithm to replace existing entries with new data objects when the data cache is full.

The DOSM also maintains a state table 630. In general, the state table 630 provides the state of the system by storing information on the overall capacity and health of the intelligent storage nodes 340. In one embodiment, the state tables are built using the multicast protocol to obtain, from the intelligent storage nodes, information about the corresponding intelligent storage node. The state information indicates whether disks on the intelligent storage nodes are healthy, how much space is on the disks, etc. In one embodiment, as shown in Figure 6, state table 630 stores: read- write state of the storage nodes; health of the storage nodes (including an identification of failed nodes); and the current load of the storage nodes, including available storage capacity and the number of input/output (“I/O”) operations per second. The DOSM uses state information to select, in an upload operation, the appropriate intelligent storage node for storage of a new object file. For example, the DOSM uses information on the number of input/output (“I/O”) operations per second to load balance the storage nodes. The DOSM also uses information on available storage capacity to select an intelligent storage node to store a new object file.

Figure 7 is a block diagram illustrating one embodiment for an intelligent storage node. For this embodiment, the intelligent storage node is implemented on a computer, including software to perform the functions described herein. An intelligent storage node 700 includes a processing core 710 that consists of one or more central processing units (“CPUs”). In one embodiment, the processing core 710 comprises two CPUs. The intelligent storage



node 700 also includes volatile memory, labeled 730 in Figure 7. The memory 730 is used to store instructions executed by the processing core 710, as well as data used by the intelligent storage node. The intelligent storage node 700 further includes a network interface 720 to interface the intelligent storage node to the plurality of distributed object storage managers 320 via the interconnect fabric 330. The elements of the intelligent storage node 700 communicate via a computer transport mechanism 750 (e.g., a peripheral component interconnect (“PCI”) bus, processor bus, etc.). The computer transport mechanism 750 is intended to represent a broad category of one or more computer busses, such as peripheral component interconnect (“PCI”) bus or the industry standard association (“ISA”) bus.

The intelligent storage node 700 further includes a plurality of disk drives 740 to store the object files. As shown in Figure 7, the number of disks in an intelligent storage node is represented as “n”, such that “n” is an integer value greater than one. In one embodiment, the processing core 710 communicates with the disk drives 740 using the ISA protocol. However, any protocol used to access disk drives, including standard computer serial interface (“SCSI”) protocol, may be used without deviating from the spirit or scope of the invention.

The intelligent storage node contains information to identify object files that it stores. In one embodiment, the information to identify object files is stored in the file system directory of the intelligent storage node. In other embodiments, the information to identify object files is cached. Table 5 illustrates example entries to cache the identification of object files in an intelligent storage node.

**Table 5**

<b>FILE ID</b>	<b>DISK ID</b>
File1.MD5	1
File6.MD5	2
File4.MD5	2
File5.MD5	“n”

5  
10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995

Table 5 includes a file identifier and a disk identifier. The file identifier, or file ID, stores the unique file handle corresponding to the object file. In one embodiment, the unique file handle is the object fingerprint obtained from performing an MD5 hash function on the contents of the object file. For the first example entry in Table 5, the unique file handle is represented as “file1.MD5.” The second column, labeled disk id, identifies the specific disk drive on the intelligent storage node that stores the object file. For the second example entry in Table 5, the object file, “file6.MD5”, is stored on the second disk drive on that intelligent storage node. On initial start-up of the intelligent storage node, the intelligent storage node builds the file identification table.

The storage cluster also processes upload requests. Figure 8 is a flow diagram illustrating one embodiment for processing upload requests in the storage cluster. For purposes of nomenclature, the “source”, as used herein, refers to the source of the object file for the upload operation. If the storage cluster receives an upload request, then the load balancing fabric 320 (Figure 3) selects an available DOSM to process the upload request (blocks 805 and 810, Figure 8). The VFS creates a file identification (*e.g.*, storage system

node) and the appropriate directory for the new object file (block 805, Figure 8). The selected DOSM parses the upload request to extract the certificate, object file, as well as client and directory information (block 820, Figure 8). If the upload request does not authenticate, then the DOSM transmits an error message to the source (block 835, Figure 8). Alternatively, if the upload request does authenticate, then the DOSM selects at least one intelligent storage node to store the object file (block 840, Figure 8). In one embodiment, the upload operation stores the object file in two storage nodes. The “mirroring” of the object files ensures accessibility to the object in the event a failure occurs in an intelligent storage node. In one embodiment for “mirroring” the object files, the network storage system stores the object file at different geographic locations (*e.g.*, different storage centers). If access to the geographically disparate storage center is unavailable at the time the object file is uploaded, then an additional copy of the file is stored at the local storage center.

In one embodiment, the DOSM uses a state table (Figure 6) to select the intelligent storage nodes most appropriate to store the new object. For purposes of discussion, the selected intelligent storage nodes are referred to herein as the “destination intelligent storage nodes.” The DOSM establishes a connection with the destination intelligent storage node (block 850, Figure 8). In one embodiment, the DOSM establishes a DOSP point-to-point connection with the destination source node. The object file is then transferred to the destination intelligent storage node (block 860, Figure 8). In addition, after transferring the file to the intelligent storage node, the DOSM receives a status message as part of the DOSP point-to-point protocol. The status message indicates whether the transfer operation was successful.

In one embodiment, the destination intelligent storage node generates a unique fingerprint for the object file (block 870, Figure 8). Specifically, the destination intelligent storage node computes an MD5 hash of the contents of the object file. The intelligent storage node also verifies the object file. After receiving the successful status at the DOSM, the DOSM establishes a connection to the virtual file system ("VFS"). The DOSM communicates file information (*e.g.*, the 128 bit.MD5 unique object fingerprint, file size, etc.), directory information (*e.g.*, folder ID, parent folder ID, etc.), as well as client information and metadata (block 880, Figure 8). The VFS attempts to verify the upload. If the VFS does not verify the upload, then an error message is sent to the source of the upload request (blocks 890 and 835, Figure 8). If the VFS does verify the upload, then the verification is transmitted to the DOSM. In turn, the DOSM verifies the upload to the source (block 895, Figure 8). Also, the storage system returns, to the source, a file handle that uniquely identifies the file to the network storage system.

If the source of the upload request is an end-user, then the DOSM re-directs the end-user to the client. For example, the DOM may redirect the end-user to a predetermined URL at the client's web site. In other embodiments, if the source was a storage port, then the DOSM transmits a storage system node (*i.e.*, handle used only for the storage system) and the unique object file fingerprint.

As discussed above, as part of the upload operation, the network storage system generates a unique fingerprint of the object file. Figure 9 is a flow diagram illustrating one embodiment for generating unique fingerprints of object files. First, the destination intelligent storage node creates a temporary file with the contents of the object file (block 900, Figure 9).

An MD5 hash calculation is performed on the contents of the temporary file (block 910, Figure 9). The DOSM determines whether the unique fingerprint, generated from the MD5 hash operation, currently exists in the network storage system (block 920, Figure 9). If the fingerprint currently exists, the temporary file, which holds the contents of the object, is deleted (blocks 930 and 940, Figure 9). Also, a reference count associated with the existing fingerprint file is incremented (block 950, Figure 9). The use of reference counts is described more fully below in conjunction with a discussion of the delete operation. If the fingerprint generated from the temporary file does not exist, then the temporary file is converted to a permanent file, and the unique fingerprint is used to identify the file in the storage cluster (block 960, Figure 9).

#### Virtual File System:

In one embodiment, directory operations are performed in the virtual file system ("VFS"). Figure 11 is a block diagram illustrating one embodiment for implementing a VFS for use with a network storage system. In general, the VFS is the control path for maintaining the network storage system. The VFS maintains, for each object file, the customer file directory including the customer assigned filenames and the unique network storage system file identifiers. In one embodiment discussed above, the unique network storage system file identifiers consist of a 128 bit digital fingerprint obtained from performing an MD5 hash calculation on the contents of the object file. As shown in Figure 11, the VFS consists of distributed directory managers ("DDMs") 1110 and distributed directories 1120. There are "n" DDMs and "n" distributed directories, wherein "n" represents any integer one or greater. In one embodiment, each client is mapped to a distributed directory.

The DDMs support common directory operations, such as “open file”, “move file”, “delete file”, “open folder”, “move folder”, and “create folder.” The arrows of Figure 11 depict multi-directory requests and operations. The requests may originate from the end-user or the client, via a storage port or a web store. In one implementation, the requests to the VFS are transported using HTTP requests and encoded using the eXtended markup language (“XML”). Although the VFS is described using the HTTP protocol with XML encoded requests, any network protocol with any type of request format may be used without deviating from the spirit or scope of the invention.

In one embodiment, the VFS employs a database to implement the file system. For the database implementation, each directory operations request is converted into the database operation. Alternatively, the VFS may implement the file system using a local file system (*i.e.*, a file system local to the VFS). For the file system embodiment, files are generated to store information stored in the database implementation. Also, the DDMs include a lookup table to locate the files in the distributed directories. The files or database tables are replicated in a remote storage center.

The network storage file system consists of files arranged in directories or folders (hereafter referred to as folders). Similar to most file systems, the network storage file system is a hierarchical file system. In a hierarchical file system, directories or folders are arranged in levels, starting with a root or base folder. Additional folders or sub folders are then arranged under the root folder. The file system may comprise any number of levels, such that additional layers of sub folders fall beneath other sub folders. For purposes of nomenclature

used herein, a parent folder to a folder is the folder arranged above the folder in the hierarchy of folders or directories.

Figure 12 illustrates example database tables for implementing the file system with a database. For the database embodiment, the VFS maintains a customer table 1200, folder table 1210 and file table 1220. The customer table 1200 includes fields for “customer ID”, “customer name”, and “customer reserved fields.” The customer ID is a network storage system identifier used to uniquely identify the client. The customer name is the real name associated with a customer. For the first example entry in the customer table 1200, “customer A” has a customer ID of “1.” The customer reserved fields provide storage reserved for use by the client.

The folder table 1210 includes fields for “customer ID”, “folder ID”, “folder parent ID”, and “metadata.” For this embodiment, each entry in the folder table corresponds to a folder in the network storage file system. The customer ID, the same customer ID stored in the customer table, uniquely identifies the client. For the example entries in folder table 1210, the customer ID of “3” identifies that the folders have been assigned to “customer C.” The folder ID identifies the specific folder for that entry. For example, the first entry in folder table 1210 is for a folder identified by the identification of “2.” The third column, labeled “folder parent ID”, identifies the parent folder for the folder corresponding to the database entry or row. For example, the second entry in folder table 1210 is a sub folder to the first entry of table 1210 (i.e., folder “100” is in the next hierarchical level beneath folder “2”). Note that the first entry in folder table 1210 does not have a value for the folder parent ID. This signifies that folder “2” is a root folder.

The file table contains an entry for each object file stored in a network storage file system. The example file table 1220 includes columns or fields for “customer ID”, “file handle”, “folder ID”, “folder parent ID”, and “metadata.” Again, the customer ID identifies the customer that owns the file. The entries shown in file table 1220 are for files stored by customer C. The file handle field stores the fingerprint that the network file system uses to uniquely identify the file. Although the network file system stores 32 byte hexadecimal character sequences to identify files, for purposes of illustration, file handle entries for file table 1220 are shown as “52.MD5”, “55.MD5”, “99.MD5”, and “67.MD5.” The folder ID field identifies the folder that contains the file. For example, the first entry in file table 1220, corresponding to file “55.MD5”, is organized or stored in folder 100. The folder parent ID identifies the parent folder to the folder that stores the file. The folder 100, which contains “52.MD5”, has a parent folder of “2.”

Figures 13A and 13B are flow diagrams illustrating one embodiment for performing directory operations in the VFS. When a DDM receives a directory operation request, the DDM parses the request to extract the certificate, an operational code, as well as arguments corresponding to the operational code (blocks 1300 and 1310, Figure 13A). The operational code specifies the directory operation requested. The DDM, using the certificate and the information contained in the request, validates the request. If the request does not validate, the DDM sends an error message to the requester (blocks 1320 and 1330, Figure 13A). Alternatively, if the request does validate, the DDM parses the operational code and extracts the arguments, including the folder to perform the open operation (blocks 1320 and 1330, Figure 13A).



In general, if the operation is for an “open folder” operation, then the DDM returns all sub folders and files contained in the folder identified by the argument. Specifically, the DDM extracts, from the appropriate distributed directory, the file and folder tables that correspond to the folder identified as an argument in the “open folder” request (blocks 1340 and 1345, Figure 13A). Specifically, the DDM extracts all the files and sub folders that correspond to the folder identified as an argument with the request. Using the example of Figure 12, if the “open folder” request included the arguments “folder ID = 2” and “customer ID = 3”, then the DDM extracts, from the folder table in the distributed directory, folder IDs 100 and 251 (*i.e.*, folders 100 and 251 are sub folders of the root folder 2). If the “open folder” request included the arguments “folder ID = 100”, then the DDM extracts from the file table file handles “52.MD5” and “55.MD5.”

If the operational code in a directory request is for an “open file” operation, subsequent to an “open folder” request, then file information is obtained from the file table (*i.e.*, file handle) and the client table (*i.e.*, client identification) to construct an authentication certificate and an SRL for the file. For the above example, if the argument with the “open file” operation specified the file “52.MD5”, then file and client information are obtained to construct the SRL for the “52.MD5” file.

If the operational code in a directory request is for a “move folder” operation, then a database operation is performed to revise the entries in the file and folder tables to reflect the new location of the folder. The “move folder” operation includes, as an argument, the new destination for the folder. Using the example of Figure 12, if the “move folder” operation specified moving folder ID 166 from a sub folder of folder ID 251 to directly beneath the root

folder 2, then the parent folder ID on the fourth entry of folder table 1210 is modified from “251” to “2.” Also, for file table 1220, the parent folder ID for the third and fourth entries are modified from “251” to “2.”

If the directory operation is a “create folder” operation, then a new entry or row is generated for the folder table (blocks 1360 and 1365, Figure 13A). The “create folder” operation includes a parent folder as an argument. As described below, the client’s folder name is converted to the network storage system’s folder identification. Using the example of Figure 12, if the requester desires to create a new folder under the sub folder 166, then the DDM assigns a new folder identification for the folder, and enters a new row or entry for the folder table 1210 with a folder parent ID of 166.

If the directory operation is a “move file” operation, then a database operation is performed to revise an entry in the file table to reflect the new location of the file (blocks 1370 and 1375, Figure 13A). The “move file” operation includes a new destination for the file as an argument in the directory request. For the example database tables in Figure 12, if the “move file” operation specified moving file “52.MD5” from folder 100 to folder 166, then the folder ID and folder parent ID fields for the first entry of file table 1220 are revised to “166” and “251”, respectively.

As shown in block 1390 of Figure 13A, the arguments extracted from the database tables are returned to the requester. In one embodiment, the response from a DDM includes XML encoded documents with the list of files (*i.e.*, in the form of a SRL) and/or directories.

For example, in response to the “open folder” request, the VFS returns file and folder Ids for the files and subfolders arranged under the subject folder.

Figure 13B is a continuation of the flow diagram of Figure 13A illustrating additional file system operations in the VFS. If the operational code is a “delete folder” operation, then the corresponding folder entry is deleted from the folder table (blocks 1372 and 1374, Figure 13B). If the operational code designates a “delete file” operation, then the file entry, identified in the operation, is deleted from its file table (blocks 1376 and 1378, Figure 13B). For a “create file” operation, the VFS adds an entry for a new file in the file table (blocks 1386 and 1388, Figure 13B). If the operational code specifies an “update folder” operation, then the client metadata in the corresponding folder table for the folder entry is updated (blocks 1386 and 1388, Figure 13B). For an “update file” operation, the VFS updates client metadata in the table for the corresponding file entry (blocks 1392 and 1394, Figure 13B). After executing the appropriate database operation, the arguments for the operation are returned to the requester (blocks 1396, Figure 13B).

In one embodiment, the network storage system uses a reference count to manage uploading and deleting existing files. In general, when a new file is uploaded to the network storage system or a file request is received to upload an existing file, the reference count is incremented by one. Conversely, when a file request is received to delete a file, the reference count is decremented by one. The network storage system uses the reference count to delete an object file when the reference count is zero. For example, a client may transmit a first request to upload an object file, entitled “my file.” After the upload operation is complete, the reference count to “my file” is one. Thereafter, a client may transmit a second request to

upload “my file.” Instead of storing a second copy of “my file”, the network storage system increments the reference count of “my file” to “2.” For this example, the client may then transmit a first request to delete “my file.” In response to this request, the network storage system does not delete “my file.” Instead, the network storage system decrements the reference count to “1.” Thereafter, if the client transmits a second request to delete “my file”, the reference count is decremented to “0”, and the network storage system deletes “my file.”

Figure 14 is a flow diagram illustrating one embodiment for the delete file operation for the network storage system. If the VFS receives a delete request, then a DDM performs a validation check (blocks 1400 and 1405, Figure 14). If the delete request is not valid, then an error message is transmitted to the requester (blocks 1410 and 1415, Figure 14). If the request is validated, then the DDM extracts a file handle (*i.e.*, MD5 file handle) from the file table in the database (block 1420, Figure 14). The DDM deletes the file identification from the file table in the database (block 1450, Figure 14). In addition, the DDM constructs a delete SRL, and transmits the delete SRL to the storage cluster (block 1460, Figure 14). In response to the delete operation, the storage cluster extracts the reference count for the corresponding file. If the reference count is greater than 1, the storage cluster decrements the reference count by one (blocks 1430 and 1440, Figure 14). Alternatively, if the reference count is one, the storage cluster decrements the reference count to zero, and deletes the file, identified by the SRL, in the appropriate intelligent storage node (block 1470, Figure 14).

### Dynamic Data Caching:

Figure 10 is a block diagram illustrating one embodiment for caching data in the storage cluster. As shown in Figure 10, there are “n” DOSMs. Each DOSM (*i.e.*, DOSM 1, DOSM 2, DOSM 3 ... DOSM “n”) contains a corresponding data cache (*i.e.*, data cache 1, data cache 2, data cache 3 ... data cache “n”). The network storage system file upload and download operations are received by the load balancing fabric 310 (also see Figure 3). A switch, such as an L4 switch, with load balancing capabilities, allocates resources among a pool of resources. For the network storage system, the load balancing fabric 310 efficiently allocates requests among the “n” DOSMs. In one embodiment, when a DOSM transfers an object from the intelligent storage node to a destination, the object is cached in the data cache of the corresponding DOSM. Objects are deleted from the data cache in order to store objects more recently requested via a least recently used (“LRU”) caching policy.

Load balancing the DOSMs in the network storage system permits an “automatic” caching of objects in high demand. In prior art systems, elaborate mechanisms are employed to identify data in high demand. Based on these decision mechanisms, data is cached in an attempt to meet the needs of the high demand. For example, an object may be in high demand when a movie studio offers, over its web site, a video preview of a newly released or upcoming film. For this example, the movie studio uses the network storage system to deliver the media rich object, “New Film Preview.” The “New Film Preview” may be available to the end-user if the end-user “clicks” on a URL in the movie studio’s web site. For this example, if the movie is very popular, when the movie studio client offers the “New Film Preview”

through its web site, many end-users may attempt to download the rich object, "New Film Preview."

For an initial request to download the object "New Film Preview", the load balancing fabric 310 selects a DOSM to manage the request. For this example, the load balancing fabric 310 selects DOSM 1 to fulfill the request. Assuming the DOSM 1 does not currently store the object in its data cache, the DOSM 1 acquires the object from the appropriate intelligent storage node. As the object is delivered to satisfy the initial request, the object is stored in the DOSM 1 data cache 1. For this example, the storage cluster receives a second request for the "New Film Preview" object, and the load balancing fabric 310, based on availability, selects DOSM 3 to process the request. Again, assuming DOSM 3 does not currently store the object in its data cache, the DOSM 3 obtains the object from the appropriate intelligent storage node, and transfers the object to the requestor as well as stores the object in the data cache 3. Similarly, for this example, additional requests are made to the storage cluster to download the "New Film Preview" object. Based on available resources, the load balancing fabric 310 selects, for two separate requests, the DOSM 2 and the DOSM "n" to handle the two requests. Again, assuming DOSM 2 and DOSM "n" do not currently store the object in their data caches, both DOSMs acquire the "New Film Preview" object from the appropriate intelligent storage node, transfer the New Film Preview to the requestor, and store the object and their respective data caches (*i.e.*, data cache 2 and data cache "n"). As illustrated by the previous example, if an object is in high demand, the storage cluster, using a load balancing fabric that selects the different DOSMs, fetches, for storage in each of the DOSM data caches, a copy of

the high demand object. Thus, the distribution of DOSM resources results in fast access to an object highly requested.

The dynamic caching of object files in the DOSM also occurs for object files retrieved from different storage centers. For example, an object file, "New Film Preview", may be stored in an intelligent storage node at storage center 1. In storage center 2, DOSMs receive requests for the object file, "New Film Preview." For this example, the DOSMs in storage center 2 retrieve the object file, "New Film Preview", from storage center 1. Similar to the example provided above, the DOSMs in storage center 2 cache the object file, "New Film Preview." Thus, object files in high demand are cached in DOSMs globally, as required by demand.

As shown in the example of Figure 10, each data cache stores potentially different objects depending upon requests processed in the respective DOSMs. For example, in addition to the "New Film Preview" object, data cache 1 stores "Photos Y" and "BLOB X"; data cache 2 stores "Ad 5" and "Video Snippet 8"; data cache three stores "Photos Z" and "Advertisement 10"; and data cache "n" stores "BLOB A" and "Video Snippet 2."

#### Geographic Replication of Storage Centers:

The network storage system is optimized to support a massive number of simultaneous download transactions. The network storage system relies upon a single virtual directory of all file objects. From any location on the Internet, clients see the exact same view of their private file system. Thus, the network storage system supports simultaneous downloads of a single object that appears identical to users worldwide. In one implementation, the network

storage system spans multiple continents with storage repositories or storage centers. The automatic geographic load balancing between storage centers ensures that all requests are directed to the nearest storage center. However, to provide fail over and enhanced performance, the storage center, including the storage cluster and VFS, are replicated. The physical replication across multiple locations includes a traffic management service. The traffic management service provides geographic load balancing of user transactions among geographic locations.

Figure 15 illustrates geographical replications of storage centers. For this example, there is a North American storage center 1510, an Asian storage center 1530, and a European storage center 1520. As shown in the example of Figure 15, clients and end-users in North America have optimal access to the storage center through the North American storage center 1510. Also, clients and end users in Europe have optimal access to European storage center 1520. Similarly, clients and end-users in Asia have optimal access to be Asian storage center 1530. In this configuration, the storage center is coupled to a wide area network to provide the maximum bandwidth for the delivery of objects. If a particular storage center becomes overloaded with requests, new requests are automatically diverted to the next closest storage center. All objects are geographically mirrored to provide one hundred percent disaster protection. Also, if access to the geographically disparate storage center is unavailable at the time a file is stored, then an additional copy of the file is stored at the local storage center (*i.e.*, the object file is mirrored locally).

The components within the network storage system are fully redundant with automatic recovery. Thus, the system supports extremely high level of service availability.



Download requests to each geographic storage center are continuously distributed across the DOSMs to deliver the fastest possible response time. In addition, in one embodiment, a global load balancing system ensures that the worldwide load across all storage centers is evenly spread to eliminate any “hot spots” and alleviate transitory demand spikes. The storage system operates far more quickly than the network itself, and thus introduces negligible delay to the overall file transit time. Thus, the worse case elapsed time for the individual object download is primarily determined by the speed of the wide area network used to transfer the object.

All components within the network storage system are replicated and redundant to provide complete recoverability in the event of a failure. In one embodiment, each storage center attaches to multiple network back bone providers to ensure continuous network access. All files and the control path directory structure are geographically replicated at the time of upload to prevent any possible loss of data. As is described more fully below, the system maintains coherency among disparate storage centers through use of the distributed object storage protocol (“DOSP”).

Figure 16 is a block diagram illustrating one embodiment for replicating the storage centers. For this example, two storage centers, labeled 1510 and 1520, are shown. However, based on the distributed architecture of the network storage system, any number of storage centers may be replicated. Storage centers 1510 and 1520 both include, for the storage cluster, load balancing fabric 320, distributed objects storage managers (“DOSMs”) 320, interconnect fabric 330, and intelligent storage nodes 340. Storage center 1510 stores the same object files as storage center 1520. For example, if “object file 1” is stored in storage

node 10 storage center 1510, then “object file 1” is stored in storage node “1” in storage center 1520. For the control path, the storage centers and 1510 and 1520 include the virtual file system (“VFS”) 50. Similarly, the VFS in storage center 1510 stores the same directory information as the VFS in storage center 1520. Accordingly, the storage centers are replicated. Although the VFS and the storage clusters are shown in the same geographic “storage center”, the VFS and storage cluster may be located at geographically disparate locations.

For this example, intelligent storage nodes in storage cluster 1510 (*i.e.*, storage node 1, storage node 2, ... storage node “n”) are accessed via Internet protocol (“IP”) addresses IP addr<sub>1</sub>, IP addr<sub>2</sub>, and IP addr<sub>n</sub>, respectively. Thus, when a DOSM communicates with an intelligent storage node in storage center 1510, the DOSM uses these IP addresses to access the specific intelligent storage node. Storage center 1520 includes storage nodes (*i.e.*, storage node 1, storage node 2, ... storage node “n”) addressed by IP address IP addr<sub>1</sub>’, IP addr<sub>2</sub>’, and IP addr<sub>n</sub>’, respectively. Thus, in storage center 1520, when a DOSM communicates with the storage node, the DOSM uses an IP addr across the interconnect fabric 330. Although the replication of storage centers is described using an TCP/IP network protocol, any network protocol and corresponding addressing scheme may be used to replicate the storage centers.

As shown in Figure 16, the distributed objects storage managers of storage center 1510 are coupled to the interconnect fabric of storage center 1520. Similarly, the distributed object storage managers of storage center 1520 are coupled to the interconnect fabric of storage center 1510. Based on this configuration, the distributed objects storage managers of storage center 1510 have access to the intelligent storage nodes of storage center 1520. Likewise, the

distributed object storage managers of storage center 1520 have access to the intelligent storage nodes of storage center 1510. As discussed above, each DOSM maintains a lookup table that correlates a file to an IP address (See Figure 6). For example, if a file specified in a download request resides on storage node 1 in storage center 1510, then an entry of the DOSM lookup table specifies IP addr<sub>1</sub>. Similarly, in storage center 1520, if a file resides in storage node 1, an entry for the DOSM lookup table specifies IP addr<sub>1</sub>'.

The storage center architecture supports a “dynamic” fail over. If a storage node, or a disk drive on a storage node, renders the access to a file inaccessible, then the DOSM may obtain the file from the replicated storage center. In one embodiment, to perform “dynamic” fail over, a mapping is stored between intelligent storage nodes in storage center 1510 and intelligent storage nodes in storage center 1520. Table 6 below shows a mapping for the example in configuration of Figure 16.

**Table 6**

<b>IP Address</b>	<b>IP Address'</b>
IP Addr <sub>1</sub>	IP Addr <sub>1</sub> '
IP Addr <sub>2</sub>	IP Addr <sub>2</sub> '
...	...
IP Addr <sub>n</sub>	IP Addr <sub>n</sub> '

For this example, IP addr<sub>1</sub> maps to IP addr<sub>1</sub>'. If there is a failure in storage node 1 in storage center 1510, then DOSMs of storage center 1510 access storage node 1 of storage center 1520 using IP addr<sub>1</sub>'. In one embodiment, the IP mapping between storage centers is

implemented by modifying only the subnet address portion between the two IP addresses mapped. For example, if IP addr<sub>1</sub> is 10.3.100.1, then IP addr<sub>1</sub>' is derived by changing, as appropriate, the subnet portion of the address (*e.g.*, 10.10.100.1).

5 The directory information stored in the VFS is replicated between storage center 1510 and 1520 in a similar manner. Thus, if a failure occurs in a distributed directory of storage center 1510, then the distributed directory manager in storage center 1510, using an IP address mapping, accesses the replicated distributed directory in storage center 1520.

10 In one embodiment, to further implement geographic replication for a fail over mode, if one disk fails, then a DOSM attempts to identify the file in the same node at a different storage center. If a storage node is rendered inoperable, then the DOSM clears the entry in the DOSM file lookup table, and attempts to locate the file at a remote storage center. For example, if disk "2" of storage node "1" in storage center 1510 fails, a DOSM 320 attempts to locate the file in storage node "1", disk "2", in storage center 1520. If the file is not located in storage node "1", disk 2, of storage center 1520, the DOSM, using the multicast protocol, attempts to locate the file locally (*i.e.*, in the storage center 1510). If the file is not located locally, the DOSM, using the multicast protocol, attempts to locate the file at a remote storage center (*e.g.*, storage center 1520).

#### Accessing The Network Storage System:

20 The network storage system has application for use in content delivery networks. In general, content owners and providers often employ the services of a content delivery network. Content delivery networks attempt to optimize the delivery of commonly accessed

rich media objects. In order to maximize the delivery of the rich media objects, content delivery networks employ local caches at the edges of the wide area network.

The network storage system has applications to complement content delivery networks by providing the underlying content for the content origin web site. In one embodiment, each  
5 cache at the content delivery network directly accesses the geographically closest storage center to locate the desired object to eliminate the need for content delivery network to access the content owner's/provider's web site.

Figure 17 illustrates one embodiment for use of the storage center in a content delivery network. For the example of Figure 17, the content delivery network 1700 includes an end-  
10 user computer 1740 coupled over a network (*e.g.*, Internet) to a content origin web server 1720. The content origin web server 1720 implements or hosts a web site. The web site permits the end-user to select content, such as rich media objects. A content delivery network includes a ("CDN") server 1730. The CDN server 1730 delivers content published on the  
15 web site by the content origin web server 1720. Specifically, the end-user computer 1740 is coupled to the CDN server 1730 to maximize the delivery of content, including rich media objects associated with the web site, to the end-user. The CDN server 1730 caches, at the CDN, a portion of the content associated with the web site 1730.

For purposes of illustration, a wide area network 1750 is shown as including satellite communication networks 1760, wireless communication networks 1770, and fiber-optic  
20 networks 1780. As illustrated in Figure 17, the CDN server 1730 is located close to the edges of the wide area network 1750. The location of CDN server 1730 close to the wide area

network 1750 optimizes the delivery of objects cached at the CDN server 1730. For this embodiment, one or more storage center(s) 1710 are coupled to the CDN server 1730. In the event of a cache miss at the CDN server 1730, the CDN server 1730 obtains the content (*e.g.*, object file) from storage center(s) 1710. This configuration allows the CDN server 1730 to  
5 bypass the slower content origin web server 1720 in the event that content, requested by end-user computer 1740, is not located at the CDN server 1730. According, the storage center(s) 1710 optimize routing of content through the Internet back to the CDN when the desired content is not located in the local cache.

Figure 18 is a flow diagram illustrating one embodiment for use of the storage center with a content delivery network. The end-user, through the end-user computer, generates an  
10 HTTP request to the content origin web server (block 1800, Figure 18). In response to the user request, the content origin server returns to the end-user computer HTML with embedded file URLs (block 1810, Figure 18). The embedded file URLs identify the rich media objects stored at the CDN server. To obtain the rich media objects, the end-user computer generates  
15 HTTP file requests to the content delivery network (*e.g.*, CDN server 1730) (block 1820, Figure 18). If the file identified by the URL is located in a cache at the CDN server site, then the CDN server delivers the file to the end-user computer (blocks 1825 and 1850, Figure 18). Alternatively, if the file is not cached at the CDN server site, the CDN server generates an  
20 HTTP file request to the storage center (blocks 1825 and 1830, Figure 18). In one embodiment, the HTTP file request includes the network storage system's SRL, to uniquely identify the file. In response to the CDN server's request, the storage center downloads the

file to the CDN cache (block 1840, Figure 18). The CDN server delivers the file to the end-user computer (block 1850, Figure 18).

#### Accessing The Network Storage System Using A Storage Port:

There are multiple ways to access the network storage system. In one embodiment, the client uses a “storage port.” The storage port provides access to the network storage system through a standard file system interface (*e.g.*, network file system (“NFS”) or Microsoft NT CIFS). The storage port may be configured by the client in various ways for different applications to optimize the delivery of rich media objects. In one embodiment, the storage port is configured at the client site to provide seamless integration from the client site to the network storage system. In another embodiment, to further off load rich media object traffic from a web site, the storage port may be used as a file system manager that downloads files to the end-user directly from the network storage system. In other embodiments, the network storage system may be directly interfaced with a private file structure.

The storage port device provides a transparent gateway connection into the network storage system. In one application, the storage port device is installed at the client site, and interfaces to local web servers via standard NFS or CIFS protocols over a local area network (“LAN”) connection. Specifically, in one embodiment, the user mounts the storage port as a storage device on the client network. In this configuration, the storage port effectively provides the user with a virtual NFS or CIFS file system with storage capacity at the storage center (*i.e.*, provides the user with hundreds of terabytes in storage capacity). In one embodiment, the storage port device occupies only approximately 1.75 inches of rack height.

As described more fully below, multiple storage ports may be installed at a single client site to increase aggregate throughput.

Figure 19 illustrates one embodiment for use of the storage port in the network storage system. An end-user 1900 communicates with a client site 1910 over a wide area network 1920. The end-user computer 1900 generates requests (*e.g.*, HTTP requests) for files accessed through the client's web site. A content web server 1925, located at the client site 1910, processes requests to the client web site, including requests to download rich media objects. Content web server 1925 is intended to represent a broad category of computers and software used to implement a web site, such as multiple web servers and/or application servers, and any hardware/software configuration may be used without deviating from the spirit or scope the invention.

The content web server 1925 is coupled to the storage port 1930 over a network, such as a local area network at the client site 1910. Specifically, the content web server 1925 generates file and directory operation requests in accordance with the format of the "local" file system. As used herein, a "local" file system connotes one or more file systems or file structures used at the client site. For example, the content web server 1925 may generate NFS or Microsoft NT CIFS requests for files and directory operations. To interface the storage port 1930 with the content web server 1925, the storage port 1930 is mounted as a storage device. In one embodiment, one directory is mounted for object files and a second directory is mounted for SRLs. As shown in Figure 19, the storage port 1930 communicates with the storage center 1950 to conduct file and directory operations.



Figure 20 is a flow diagram illustrating one embodiment for use of a storage port to deliver content. The client site receives a URL file request from an end-user computer (block 2010, Figure 20). The URL identifies an object file associated with the client's web site. In response to the end user's URL file request, the client site (*e.g.*, content web server) generates a local file system request for the object file (block 2020, Figure 20). The local file system request is received by the storage port. The storage port includes a cache to store both object files and directory information. If the object file is stored locally in the storage port, then the storage port retrieves the object file from the data cache, and returns the object file to the content web server in response to the local file system request (blocks 2030, 2040, and 2070, Figure 20). Alternatively, if the storage port does not store a copy of the object file in its data cache, then the storage port requests the object file from the storage center (blocks 2030 and 2050, Figure 20). In response to the local file system request, the storage center downloads the object file to the storage port, and the object file is returned to the content web server (blocks 2060 and 2070, Figure 20). Thereafter, the content web server delivers the object file to the end-user in response to the URL file request (block 2080, Figure 20).

The storage port may be implemented in either hardware or software. Figure 21a illustrates one hardware configuration for a storage port device. As shown in Figure 21a, the content web server 2100 communicates with the storage port 2110 over a communications link 2120, such as a local area network. The storage port 2110 conducts file and directory operations with storage center 2130.

Figure 21b illustrates embodiments for implementing the storage port in software. In one embodiment, the network storage system is accessed through library calls or through

application program interface (“API”) calls. For these embodiments, the software provides translation between the client’s local file system and the network storage file system. As discussed above, the storage center 2160 includes software running on computers for performing the functions of the VFS and intelligent storage clusters. This software includes entry points (*i.e.*, APIs) to permit interfacing of external software. In part, the APIs on the storage center software permit the client to conduct file and directory operations as described herein. As shown in Figure 21b, content web server 2140 runs, in addition to software to operate the client site, software to call APIs in the network storage center. Thus, for this embodiment, the content web server 2140 executes network storage system file and directory operations over the wide area network 2180 through remote program calls.

In another embodiment, shown as storage system library calls 2155, a customized network storage system library includes a collection of file system operations. For example, one library function may permit software operating at the client (*e.g.*, on content web server 2140) to request an object file download to the storage center through use of the library function. For this example, to perform the file download operation, the client software calls the file download function and passes the SRL as an argument to the function call. A library of functions provides an additional means to interface client software to directly access the network storage system.

Figure 22 is a block diagram illustrating one embodiment for a storage port. As shown in Figure 22, a storage port 2200 includes a processing core 2210, memory 2230, storage port data store 2240, and network interface(s) 2220. These components are coupled via a bus transport 2250 that may include one or more busses (*e.g.*, ISA, PCI, or microprocessor buses).

Processing core 2210 includes one or more central processing units (“CPUs”). In one embodiment, the storage port includes two CPUs. Memory 2330 is used to store, during operation of the device, software to perform the functions of the storage port described herein. The storage port data store 2240 contains one or more hard disk drives (*i.e.*, “n” hard disk drives, wherein “n” is any number one or greater), used, in part, to cache file system information (*i.e.*, directory cache) and object files (*i.e.*, data cache). The network interface(s) 2220, which includes “n” network interface cards, couples the storage port 2200 to client devices (*e.g.*, content web server). In addition, to support a fail over architecture, the network interface cards are used to connect one or more storage ports together. In one embodiment, the storage port includes three network interface cards.

Figure 23 is a block diagram illustrating one embodiment for file system translation in the storage port. The network storage system issues “file handles” unique to the network storage system. In one embodiment, a network storage system file handle identifies, for a corresponding file: a) client identification; b) parent directory; c) metadata and d) the unique digital fingerprint (*i.e.*, 128 bit MD5 identification). In general, the file system translation software 2300 converts local file system operations to network storage system file system operations. In one embodiment, to perform this function, the software includes file system translator 2320 and storage system access processes 2330. The file system translator 2320 includes local file system interception 2340 and storage system kernel processes 2350.

In operation, local client file system 2310, which may include operating system software running at the client’s site, issues local file system operations. For example, the client software may issue requests, in accordance with UNIX or Microsoft NT to open a file.

The file open operation includes a file descriptor that identifies the file in the local file system. Typically, file system calls are processed by the operating system kernel (labeled 2360 in Figure 23). The operating system kernel software maintains a mapping between file descriptors and directories to “inodes.” The inodes provide the system a physical pointer to the file data in the system (*e.g.*, a pointer to the file stored on a hard disk drive).

For the embodiment of Figure 23, when the local client file system 2310 issues a file system operation, local file system interception 2340 “traps” or intercepts the call, and passes the thread of execution to the storage system kernel processes 2350. In one embodiment, the local file system interception 2340 comprises CODA software, developed at Carnegie Mellon University. In general, CODA is a type of distributed file system. A portion of the functionality provided by the CODA software exports an underlying file system. Specifically, CODA exports file system operations, typically executed in the kernel level, to applications programs accessible in the user portion of memory. Although file system translation is described using CODA to intercept local file system operations, any software that intercepts file system calls may be used without deviating to the spirit or scope of the invention.

In general, the storage system kernel processes 2350 obtains network storage system file handles (referred to herein as “storage handles”) for storage in operating system kernel 2360 to provide a mapping between local file system descriptors and storage handles. Thus, the file descriptors provide a handle to identify files and directories in the local file system, and the storage handles provide a handle to identify files and directories in the network storage system.

To maintain the mapping between local file system descriptors and storage handles, the storage system kernel processes 2350 obtains network storage file system information from storage system access processes 2330. Specifically, storage system kernel processes 2350 obtains from storage system access processes 2330 storage handles and directory information. As shown in Figure 23, storage system access processes 2330 obtain directory and storage handle information from directory cache 2370. Alternatively, if directory and storage handle information is not cached at the storage port, storage system access processes 2330 query the network storage system (*i.e.*, VFS) to obtain directory information and storage handles. Accordingly, the translation system 2300 provides a mapping between the client's local file system and the network storage file system.

Figure 24 is a flow diagram illustrating one embodiment for translating a file system operation from a local file system to the network storage file system. The process is initiated by the client issuing a local file system request (block 2400, Figure 24). The local file system request is received by the operating system kernel, and dispatched to the file system translator (Figure 23). For example, if the file system operation is an open file operation for the file "foo.txt", then the operating system kernel dispatches the open file operation with the file name "foo.txt" as an argument to the file system translator. If the file system operation is an "Open Folder" operation for the folder "dir1", then the operating system kernel dispatches the open folder operation with the folder name "dir1" as an argument.

The process determines whether there is sufficient directory information in the storage port directory cache (block 2430, Figure 24). For the "Open Folder" example above, if the storage handles for all subfolders and files are not stored in the directory cache, then

additional directory information is required to fulfill the request. For the “Open File” example, if the storage port has been recently initialized and thus does not contain information on the file, then additional directory information on the file (e.g., “foo.text”) is required to open the file.

5 If there is sufficient directory information in the directory cache, and the file system operation does not require retrieving data (*i.e.*, the file system operation is not an “open file” operation) or updating directory information, then the appropriate directory information from the directory cache is retrieved and returned in response to the local file system operation (blocks 2430 and 2435, Figure 12) (blocks 2435 and 2437, Figure 24). For the “Open Folder” example above, storage handles for all subfolders and files in the subject folder are retrieved from the directory cache, the storage handles and corresponding file identifiers are stored in the operating system kernel, and the file identifiers are returned to local file system.

10 If additional directory information is required (*i.e.*, the information is not in the storage port directory cache), then a request is generated to the VFS for the additional directory information (block 2070, Figure 24). In one embodiment, the storage port generates an XML encoded request. For the “Open Folder” example, if the storage nodes and corresponding file identifiers are not stored in the directory cache, then the storage port generates an XML encoded “Open Folder” request to extract file and folder information for files and subfolders within the subject folders (*i.e.*, the folder that is the subject of the “Open Folder” request). In  
15 one embodiment, in response to a request for folder information, the VFS returns name, folder identification, client metadata, upload SRL, and parent folder identification. In response to a request for file information, the VFS returns name, file identification, client metadata,  
20

download SRL, and parent folder identification. In one embodiment, the client metadata fields are used to track and maintain state information used in the local file system (*e.g.*, information for UNIX, Microsoft Windows or NT, etc.). In addition to obtaining additional directory information, if the client local file system command is a directory operation (*i.e.*, “move folder”, “delete folder”, etc.), then an XML request to the VFS is generated to perform the directory operation in the VFS. The directory information is received and stored in the directory cache (block 2480, Figure 24).

If the file system operation requires file data (*e.g.*, open file, read file etc.), then the storage port determines whether the file is located in the data cache (block 2440, Figure 12). If the file is stored in the data cache, then the file, or appropriate portion, is transferred from the storage port to the client requestor (block 2090, Figure 12). Alternatively, if the file is not in the data cache, then the storage port generates a file download request to the storage cluster (block 2050, Figure 24). In response to the storage cluster request, the storage port receives and subsequently caches the object file in the data cache (block 2060, Figure 12). The object is then transferred from the storage port to the client requestor (block 2090, Figure 12).

#### End User Network Storage System Access Method:

In another embodiment, the storage port supports file downloads directly to the end-user or through a CDN partner. In one embodiment, the SRLs are directly embedded into the Web page HTML, and are sent to the end-user. This results in transferring objects directly from the storage center to the end-user browser. Figure 25 is a block diagram illustrating one embodiment for using the storage port to directly download object files to the end-user. For

10 this configuration, an end-user computer 2610 communicates with a client site 2620 and the  
storage center 2650. The client site 2620 maintains a web site. For this embodiment, the  
client site 2620 maintains a web site through a content web server 2630. However, any  
configuration of servers, including remote web site hosting, may be used without deviating the  
5 spirit or scope of the invention.

The content web server 2630 communicates with the storage port 2640, and in turn,  
the storage port 2640 communicates with the storage center 2650. As illustrated in Figure 25,  
the end-user, through end-user computer 2610, generates URL requests to the client site 2620,  
and receives, in return, HTML with one or more embedded SRLs. Using the embedded SRLs,  
the end-user computer 2610 generates SRL requests directly to the storage center 2650 over a  
wide area network 2660. In response, the storage center 2650 serves object files directly to  
the end-user computer 2610.

Figure 26 is a flow diagram illustrating one embodiment for directly downloading  
object files to an end-user. The client site (*e.g.*, content web server) generates local file  
system requests for SRL(s) corresponding to file(s) (block 2700, Figure 26). The file(s)  
contain content that the client desires to embed in the web page. In one embodiment, the  
storage port dynamically generates the SRL(s) in response to the request from the content web  
server (block 2710, Figure 26). In one embodiment, a time-out parameter is added to the  
SRL(s) (block 2720, Figure 26). The time-out parameter permits a client to specify a period  
20 of time that the SRL is valid (*i.e.*, a period of time that the end-user may access the file). In  
one implementation, the time-out parameter specifies a period of time with a granularity in  
seconds.



The SRL(s) are embedded in the HTML of the client's web page (block 2730, Figure 26). The end-user issues web page requests to the client site (block 2740, Figure 26). The content web server then downloads the requested HTML with the embedded SRL(s) (block 2745, Figure 26). With the embedded SRL, the end-user generates HTTP requests to the storage center (block 2750, Figure 26). If the SRL(s) do not authenticate at the storage center, then the storage center transmits an error message to the end-user (block 2755, Figure 26). If the SRL(s) do authenticate, then the time-out parameter is checked to determine whether the file access is valid (block 2760, Figure 26). If the SRL is not valid (i.e., the time-out parameter is out of range), then the operation is ceased (block 2760, Figure 26). If the SRL is within the specified time range, then the storage center downloads the object file to the end-user (block 2770, Figure 26).

The storage port 2640 acts as a file system cache. For this embodiment, the storage port contains the client's SRL files stored in a standard NFS or CIFS directory format. Each NFS or CIFS file contains the corresponding SRLs, and the SRLs contain the unique file identifier and the SRL authentication certificate.

In one embodiment, to deliver the SRLs to the end-user, the network file system utilizes a second directory, in addition to the directory for the object files, that shadows the object file directory. The client uses the second directory to obtain shadow files. A shadow file contains an SRL to identify an object file of the network storage system. In one embodiment, to embed the SRL into the web page HTML, the client reads the contents of the shadow file for the corresponding object file. In one embodiment, the shadow file is generated during an upload operation. The client may access a shadow file by mounting the

second directory. For example, a client may specify, for the file "foo.text", the following directory-filename:

storagefilesystem:/export/dir/foo.text.

The client uses this directory and filename to access the contents of the object file, "foo.text."

5 To obtain the SRL for the example file "foo.text", a client mounts a different directory, such as the following example directory:

storagefilesystem:/SRL/dir/foo.text,

wherein, the SRL file contains a unique file identifier and the SRL authentication certificate for the file, "foo.text." To deliver the SRL to the end-user, the client reads the contents of a shadow file for the corresponding object file, and publishes the SRL to the user.

#### Client Private File System Directory:

The network storage system of the present invention also supports using an existing private file directory to access the storage system. For this embodiment, the network storage system customer (*e.g.*, client) may desire to use their own file structure in conjunction with the network storage system's file system. In other embodiments, a client of the network storage system may wish to develop a file system to track additional information beyond that information tracked using NFS or CIFS.

Figure 27 is a block diagram illustrating one embodiment to interface a storage center to a client's private file directory system. In one embodiment, the storage port at the client site 2820 is replaced with a private file manager 2840. For this embodiment, the private file manager 2840 generates SRLs for object files using a unique file identification assigned to the

user file at the time of upload, as well as using a shared secret to authenticate file system operations. As shown in Figure 27, the content web server 2830, operating at the client site 2820, generates file system requests to the private file manager 2840. In turn, the private file manager 2840 issues SRLs corresponding to the object files that are the subject of the request.

5 In one embodiment, the client supplies their own unique ID at the time the client uploads files to the storage center. In another embodiment, the client utilizes, in requests to download files, the object finger print returned by the storage center.

As shown in Figure 27, the end-user, through end-user computer 2810, generates URL requests to the client's web site. In turn, the client site 2820 returns HTML with embedded SRLs. With the embedded SRLs, the end-user computer 2810 generates SRL requests, over a wide area network 2860, to the storage center 2850. In turn, the storage center 2850 serves object files identified by the SRL.

10

Figure 28 is a flow diagram illustrating one embodiment for accessing object files in a storage center using a client's private file system. The end-user issues the URL requests to the client web site (block 2900, Figure 28). In response, the client (*e.g.*, content web server) generates file location requests to a file manager (block 2910, Figure 28). In general, the file manager services requests to issue SRLs corresponding to files in the client's private file system. A client may use any type of file system in conjunction with the network storage system. All that is required is that the client's private file system issues SRLs for files managed by the client's private file system. The file manager retrieves the SRL for the file associated with the HTML, and delivers the file to the content web server (block 2920, Figure 28). The content web server then transmits to the end-user HTML with the embedded

15

20

SRL (block 2930, Figure 28). Thereafter, the end-user generates HTTP requests to the storage center with the SRL (block 2940, Figure 28). If the SRL does not authenticate, then the storage center issues an error message to the user. Alternatively, if the SRL authenticates, then the storage center generates an MD5 hash on the client supplied unique file ID to identify the file (block 2947, Figure 28). The storage center thereafter downloads the object file to the end-user (block 2950, Figure 28)

For the client's private file system access method, the client maintains a mapping between unique filenames and SRLs. In one embodiment, the unique filename is not obtained from an MD5 hash operation, but is a unique filename. Thus, the network storage system utilizes a technique to differentiate between MD5 file names, derived from the contents of the object file, and client unique file names. In one embodiment, to differentiate between these two types of file names, the network storage system assigns different storage fingerprint identifiers. For a filename generated by an MD5 hash operation on the contents of the object file, the file is designated "128bits.MD5." To identify a customer unique filename, the file is designated as "MD5.UFID" (*i.e.*, where "MD5" is the client's unique file name). This convention permits the network storage system to differentiate between the two types of file identifiers, and allows the customer to interface with the network storage system by only designating unique file names.

#### Failover Architecture:

In one embodiment, the storage port supports failover or failsafe architectures. Figure 29 is a block diagram illustrating one embodiment for a storage port fail over

configuration. For purposes of explanation, Figure 29 illustrates a fail over configuration with two storage ports. However, the storage port fail over configuration may be extended to any “2N” fail over configuration. For this embodiment, the fail over configuration includes an active storage port 3010 and a passive storage port 3020. Each storage port includes a plurality of network interface cards. Both the active storage port 3010 and passive storage port 3020 communicate to storage center(s) over wide area network 3065, through network interface cards 3045 and 3025, respectively. The active storage port 3010 and passive storage port 3020 also communicate to the client site network via network interface cards 3050 and 3035, respectively. As shown in Figure 29, the client accesses the active storage port 3010 over client site network 3060 using IP Addr.

For the embodiment of Figure 29, a third network interface card is contained on both the active storage port 3010 (3055) and passive storage port 3020 (3030) to communicate between the devices for fail over monitoring. The active storage port 3010 operates as current storage port at the client site. The passive storage port 3020 monitors the health of the active storage port 3010. Specifically, active storage port 3010 includes health monitoring 3070 that continually executes a process to ascertain the health of the active storage port 3020 (*e.g.*, health of the CPUs, hard disk drives, etc.). For this embodiment, the passive storage port 3020 queries the active storage port 3010 for health status. If a condition occurs in the active storage port 3010 that warrants a fail over condition, then the passive storage port 3020 becomes the active storage port (*i.e.*, the passive storage port is used to interface the client site to storage center(s)).

In one embodiment, to support fail over, one IP address is used for the NFS/CIFS export. For this embodiment, a standard IP switch over scheme may be utilized. Specifically, when a fail over condition occurs, the passive storage port 3020 assumes the IP address of the active storage port 3010. The health monitoring 3070 and 3080 include both active and passive processes, so that if a fail over condition occurs, the passive storage port may execute the active storage port process.

Figure 30 is a flow diagram illustrating one embodiment for a storage port fail over process. When a storage port fail over occurs, the new storage port does not contain any directory information in its directory cache or any objects in its data cache. Thus, after a fail over operation, if a file is open and the storage port receives a read file request, the new storage port must execute a file open operation (blocks 3130 and 3140, Figure 30). After the storage port receives the file identification information (*e.g.*, SRL), the storage port generates a request to the storage center to obtain the object file, in order to transmit a block of object data in response to the read file request.

After a fail over condition, when a file is requested (block 3120, Figure 30) or an open file operation is necessary, the storage port generates an XML to the VFS to obtain file identification information (block 3150, Figure 30). In response, the VFS returns file identification information (block 3160, Figure 30). With the file identification information, the storage port updates its directory cache (block 3170, Figure 30). With the file identification information (*e.g.*, SRL), the storage port generates a request to the storage center for the object file (block 3180, Figure 30). In response, the storage center delivers the object file, and the storage port updates its data cache (block 3190, Figure 30). If the storage center

download operation was in response to a read request to the storage port, the read request delivers data as specified in the read request.

#### Network Storage System Dynamic Failover:

5 In one embodiment, storage nodes monitor the health of their respective nodes (*e.g.*, monitor hard disk drives, processor, network access, etc.). If the health of a storage node requires that the storage node should cease operation, then the storage cluster executes a fail over operation. In one embodiment, in a fail over operation, the storage node reports the failed status to the DOSMs, and the DOSMs update their state table. If this occurs, the DOSMs attempt to locate the replicated file at a different storage node (*i.e.*, either locally or remotely).

10 Figure 31 is a flow diagram illustrating one embodiment for using the multicast protocol after a storage node fail over condition. If a storage node fails, then the DOSMs update and their state tables to indicate that the storage node is no longer in use (blocks 3210 and 3220, Figure 31). If the DOSM receives a file request for a file previously stored on the failed storage node, then the DOSM, which received the download request, issues a multicast protocol request to the storage nodes (blocks 3225 and 3230, Figure 31). In one embodiment, the DOSM may issue the multicast protocol request to local storage nodes (*i.e.*, storage nodes located at its storage center).

15 Each storage node that receives the multicast request determines whether it contains the requested object file (block 3240, Figure 31). If none of the storage nodes contain the object file, then the DOSM may issue another multicast protocol request at a remote storage

location (blocks 3245 and 3247, Figure 31). Again, at the remote storage center, each storage node determines whether it contains the requested object file (block 3240, Figure 31). In another embodiment, if the DOSM does not locate the file using the multicast protocol, the DOSM may query each individual storage node using the DOSP point-to-point protocol.

5           When a storage node locates the requested object file, the storage node broadcasts the file identification information using the multicast protocol (block 3250, Figure 31). Each DOSM snoops, using the multicast protocol, to receive the file identification information (block 3260, Figure 31). As illustrated in the process embodiment of Figure 31, the multicast protocol may be used to synchronize file location information in the DOSMs in the event of a fail over condition.

#### Multi-Cast Protocol:

10           The multi-cast protocol of the present invention supports the maintenance of file information in a distributed storage system. Since the network storage system consists of a plurality of storage nodes, the multicast protocol is used to track file information and synchronize file information throughout the network storage system. The tracking and  
15           maintaining of file and directory information includes maintaining information throughout geographically disparate storage centers. In one embodiment, the multi-cast protocol synchronizes cache information in the DOSMs. For example, if a new object file is loaded, the multi-cast protocol provides a means for all DOSMs in the network storage system to  
20           obtain information necessary to access the new object file. In addition, some file operations, including delete file or update file operations, require updating the DOSM lookup tables.



Also, if a storage node fails, and a fail over condition is executed, the multi-cast protocol provides a means for the DOSMs to locate the file at the storage node the file has been replicated.

#### The Distributed Object Storage Protocol (DOSP):

5           In one embodiment, the DOSP includes daemon/master services and multicast-based monitoring communications. Communication between the daemon and master components is accomplished through a set of “request packets” and “response packets.” The request packets consist of three major subcomponents: an opcode that specifies the type of request; a header implemented via a C++ specific structure that provides information about the data that follows; and data transmitted, if any.

10           Each operation has an associated operation code and a pair of structures: one for issuance of the request, and a second separate structure for return values. Once the receiver has received and processed the request (sent data, deleted file, etc) it then sends a response consisting of the appropriate “Out Structure” indicating the status of the request (SUCCESS, FAILURE, etc) and any required return values. Currently, there are six service operations supported by the DOSP: null, store file, retrieve file, retrieve file range, delete file, and get contents.

15           The null operation provides a framework to develop future modifications of the protocol and to test basic functionality of the master/daemon request/response interaction.

20           When a file is ready for storing, the DOSM client sends a request id, followed by a request header. It then sends the data to the dosd in a series of chunks, each of which is

preceded by a DosdStoreHeader which gives the size of the next chunk to be read, and a field indicating whether this is the last packet to be sent.

When a file is being retrieved from the Storage Cluster, the DOSM client sends a request Id, followed by a request structure. The DOSD responds by first sending the size of the data, the data requested, and finally an Out structure with the return value of the operation.

The get contents operation is used to acquire the contents of the storage node as a character based stream. The after the "In Structure" is passed to the dosd, the dosd first returns the length of the stream of md5 hash/node&disk associations, followed by the stream of data, with the "Out structure" coming last.

The DOSP provides an extensible framework for any new services or additional functionality. There are essentially three steps to adding new functionality: defining a new pair of In/Out structures; assigning a new opcode, implementing a handle in the DOSM client; and adding a service handle for the dosd.

To facilitate gathering of information about the system, the DOSP provides several multicast-based services. In one embodiment, these services work in a manner very similar to the non-multicast aspect of the protocol. Specifically, requests consist of three parts: an opcode; a request In structure; and any additional data.

Responses consist of a response structure containing a RETURN value and any other return values required to satisfy the request. If data is streamed, a size field precedes the data, followed by the data, and then followed by the Out structure.

Since multicast traffic occurs on a completely separate port from point-to-point dosm/dosd traffic, the multicast In/Out structures are not multicast-specific. This makes it possible for the DOSM to query the entire dosd storage cluster or to query an individual machine with the same request/response structures and their associated operational sequencing.

One of the jobs of the DOSM is to monitor the current state of nodes in the cluster. There are several tools to facilitate this task. Primarily, the various dos daemons multicast heartbeats on a specific multicast port and group. The DOSM contains an option to query a specific disk, or all of the disks on a given a storage node. A “get disk state” function returns a value, and an array of disk state values (online, offline, down) with one entry per disk. A “get disk status” function contains an option to query a specific disk, or all of the disks on a given a node. The “get disk status” contains a RETURN value, and an array of disk statistics; one array per statistic (bytes free, bytes available, inodes used, inodes available, number of outstanding ops), with one entry per disk. The DOSP includes a load balancing function.

The DOSP includes a heartbeat function. This allows querying specific machines for a heartbeat in addition to providing system-wide tracking functionality via multicast methods.

Although the present invention has been described in terms of specific exemplary embodiments, it will be appreciated that various modifications and alterations might be made by those skilled in the art without departing from the spirit and scope of the invention.